



Amendment

SN: 09/862,914; Docket Number: DJM-0001; Magine, et al.

Claims

1. (Original) An underwater alert system comprising:

a first transmitter assembly, adapted to be carried by a first diver, including:

at least a first alert switch adapted to generate at least a first electrical alert actuation

5 signal responsive to the at least the first alert switch being actuated;

a first transmitter electrically coupled to the at least the first alert switch and adapted to generate at least a first predetermined electrical transmit signal responsive to receiving the at least the first electrical alert actuation signal, respectively;

10 a first transmitting element electrically coupled to the first transmitter and adapted to generate at least a first predetermined wireless signal responsive to receiving the at least the first predetermined electrical transmit signal, respectively; and

a first waterproof transmitter housing adapted to carry at least one of the at least the first alert switch, the first transmitter and the first transmitting element; and

15 a first receiver assembly, adapted to be carried by a second diver having a first mask adapted to be worn on the second diver's head, including:

a first receiving element adapted to generate at least a first electrical receive signal responsive to receiving the at least the first predetermined wireless signal, respectively;

20 a first receiver electrically coupled to the first receiving element and adapted to generate at least a first predetermined electrical alert attention signal responsive to receiving the at least the first electrical receive signal, respectively;

at least a first alert device electrically coupled to the first receiver and adapted to generate at least a first predetermined alert responsive to receiving the at least the first predetermined electrical alert attention signal; and

25 a first waterproof receiver housing adapted to carry at least one of the first receiving element, the first receiver and the at least the first alert device;

wherein the first mask is adapted to carry at least the at least the first alert device of the first receiver assembly in a way that permits the at least the first predetermined alert to gain the attention of the second diver when the first mask is worn on the second diver's head.

30

2. (Currently Amended) The underwater alert system according to claim 1, wherein the at least the first alert switch further comprises:

at least a first pushbutton switch adapted to generate the at least the first electrical alert actuation signal responsive to the at least the first pushbutton switch being manually actuated by the first diver.

813. (Represented - formerly dependent claim # 81) The underwater alert system according to claim 2, wherein the first transmitter assembly further comprises:

a light source carried by the first transmitter housing and adapted to illuminate at least a portion of the pushbutton.

34. (Currently amended) The underwater alert system according to claim 1, wherein the at least the first alert device further comprises:

a visual alert device adapted to generate a predetermined visual alert, as the at least the first predetermined alert, that the second diver can see when wearing the first mask.

45. (Currently amended) The underwater alert system according to claim 34, wherein the visual alert device further comprises:

a first light source adapted to generate a predetermined visible light signal, as the predetermined visual alert.

56. (Currently amended) The underwater alert system according to claim 1, wherein the at least the first alert device further comprises:

an audible alert device adapted to generate a predetermined audible alert, as the at least the first predetermined alert, that the second diver can hear when wearing the first mask.

67. (Currently amended) The underwater alert system according to claim 56, wherein the audible alert device further comprises:

an electro-acoustic transducer adapted to generate a predetermined audible acoustic signal, as the predetermined audible alert.

78. (Currently amended) The underwater alert system according to claim 1, wherein the at least the first alert device further comprises:

a tactile alert device adapted to generate a predetermined tactile alert, as the at least the first predetermined alert, that the second diver can feel when wearing the first mask.

89. (Currently amended) The underwater alert system according to claim 78, wherein the tactile alert device further comprises:

a vibrator adapted to generate a predetermined vibration signal, as the predetermined tactile alert.

910. (Currently amended) The underwater alert system according to claim 1 further comprising: a second transmitter assembly adapted to be carried by the second diver and including:

at least a second alert switch adapted to generate at least a second electrical alert actuation signal responsive to the at least the second alert switch being actuated;

a second transmitter electrically coupled to the at least the second alert switch and adapted to generate at least a second predetermined electrical transmit signal responsive to receiving the at least the second electrical alert actuation signal, respectively;

a second transmitting element electrically coupled to the second transmitter and adapted to generate at least a second predetermined wireless signal responsive to receiving the at least the second predetermined electrical transmit signal, respectively; and

a second waterproof transmitter housing adapted to carry at least one of the at least the second alert switch, the second transmitter and the second transmitting element; and

a second receiver assembly, adapted to be carried by the first diver having a second mask adapted to be worn on the first diver's head, including:

a second receiving element adapted to generate at least a second electrical receive signal responsive to receiving the at least the second predetermined wireless signal, respectively;

a second receiver electrically coupled to the second receiving element and adapted to generate at least a second predetermined electrical alert attention signal responsive to receiving the at least the second electrical receive signal, respectively;

at least a second alert device electrically coupled to the second receiver and adapted to generate at least a second predetermined alert responsive to receiving the at least the second predetermined electrical alert attention signal; and

5 a second waterproof receiver housing adapted to carry at least one of the second receiving element, the second receiver and the at least the second alert device; and

wherein the second mask is adapted to carry at least the at least the second alert device of the second receiver assembly in a way that permits the at least the second predetermined alert to gain the attention of the first diver when the second mask is worn on the first diver's head.

10 ~~4011.~~ (Currently amended) The underwater alert system according to claim ~~910~~,₁

wherein the first waterproof transmitter housing and the second waterproof receiver housing are integrally formed together to provide a first transceiver housing adapted to be carried by the second mask, and

15 wherein the second waterproof transmitter housing and the first waterproof receiver housing are integrally formed together to provide a second transceiver housing adapted to be carried by the first mask.

~~4112.~~ (Currently amended) The underwater alert system according to claim ~~4011~~,₂

20 wherein the first transceiver housing is integrally formed with the second mask, and wherein the second transceiver housing is integrally formed with the first mask.

~~4213.~~ (Currently amended) The underwater alert system according to claim 1 further comprising:

25 a first attachment mechanism adapted to permit the first waterproof receiver housing to be mechanically coupled to the first mask.

~~4314.~~ (Currently amended) The underwater alert system according to claim ~~4213~~, wherein the first attachment mechanism further comprises:

30 a first bracket adapted to be carried by the first mask and having a first mounting interface adapted to mechanically engage and disengage a first mounting interface on the first waterproof receiver housing to permit the first waterproof receiver housing to be attached to and removed from, respectively, the first bracket.

4415. (Currently amended) The underwater alert system according to claim 13-14, wherein the first bracket further comprises:

5 a second mounting interface having an adhesive disposed thereon to permit the second mounting interface of the first bracket to be mechanically coupled to the first mask.

4516. (Currently amended) The underwater alert system according to claim 13-14, wherein the first bracket is integrally formed with the first mask.

10 4617. (Currently amended) The underwater alert system according to claim 12-13, wherein the at least the first alert device generates the first predetermined alert when the first waterproof receiver housing is mechanically coupled to the first mask, and wherein the at least the first alert device generates a second predetermined alert when the first waterproof receiver housing is mechanically decoupled from the first mask.

15 4718. (Currently amended) The underwater alert system according to claim 1, wherein the first waterproof receiver housing is integrally formed with the first mask.

4819. (Currently amended) The underwater alert system according to claim 1,

20 wherein the first transmitter assembly further comprises a first transmitter identity selection device adapted to provide the first transmitter with at least a first transmitter identity, and

wherein the first receiver assembly further comprises a first receiver identity selection device adapted to provide the first receiver with the at least the first transmitter identity to permit the first receiver to communicate with the first transmitter.

25 4920. (Currently amended) The underwater alert system according to claim 1,

wherein the first transmitter assembly further comprises:

a first power supply adapted to provide a first supply of electrical power; and

a first power switch adapted to electrically couple the first supply of electrical power to at

30 least one of the at least the first alert switch, the first transmitter and the first transmitting element responsive to the first power switch being actuated; and

wherein the first receiver assembly further comprises:

a second power supply adapted to provide a second supply of electrical power; and

a second power switch adapted to electrically couple the second supply of electrical power to at least one of the first receiving element, the first receiver and the at least the first alert device responsive to the second power switch being actuated.

2021. (Currently amended) The underwater alert system according to claim ~~19-20~~, wherein at least one of the first power switch and the second power switch further comprises:

a water-activated switch adapted to be actuated responsive to the water-activated switch being located underwater.

~~21~~22. (Currently amended) The underwater alert system according to claim 1 further comprising:

a dive computer adapted to generate dive computer data, electrically coupled to the first transmitter, and adapted to be carried by the first diver,

wherein the at least the first alert switch further comprises:

an electronic switch electrically coupled to the dive computer and adapted to generate the at least the first electrical alert actuation signal responsive to the dive computer data being an undesirable, predetermined value.

~~22~~23. (Currently amended) The underwater alert system according to claim 1 further comprising:

a dive computer adapted to generate dive computer data, electrically coupled to the first transmitter, and adapted to be carried by the first diver,

wherein the first transmitter is adapted to transmit dive computer data, associated with the dive computer, to the first receiver.

8224. (Represented - formerly dependent claim # 82) The underwater alert system according to claim 1, wherein the first transmitter assembly further comprises:

a transmitter alert device adapted to generate at least a second predetermined alert responsive to a function of the first transmitter assembly.

8325. (Represented - formerly dependent claim # 83) The underwater alert system according to claim 82-24, wherein the function of the first transmitter assembly further comprises at least one of:

a low voltage warning, a verification of operation, a confirmation of transmitter identity selection, a confirmation of activation of the first alert switch, a confirmation of activation of the power on/off switch, and a condition of the charging circuit.

8426. (Represented - formerly dependent claim # 84) The underwater alert system according to claim 82-24, wherein the transmitter alert device further comprises at least one of:

a visual alert device adapted to generate a predetermined visual alert, as the at least the second predetermined alert, that the first diver can see when wearing the first transmitter assembly;

an audible alert device adapted to generate a predetermined audible alert, as the at least the second predetermined alert, that the first diver can hear when wearing the first transmitter assembly; and

a tactile alert device adapted to generate a predetermined tactile alert, as the at least the second predetermined alert, that the first diver can feel when wearing the first transmitter assembly.

8527. (Represented - formerly dependent claim # 85) The underwater alert system according to claim 1, wherein the at least the first alert switch is automatically actuated responsive to information related to at least one of the first diver's body, equipment and environment.

8628. (Represented - formerly dependent claim # 86) The underwater alert system according to claim 1, wherein the at least the first alert device generates the first predetermined alert when the first waterproof receiver housing is above water, and wherein the at least the first alert device generates a second predetermined alert when the first waterproof receiver housing is underwater.

2329. (Currently Amended) An underwater alert system comprising:

a first transmitter assembly, adapted to be carried by a first diver, including:

at least a first alert switch adapted to generate at least a first electrical alert actuation signal responsive to the at least the first alert switch being actuated, wherein the at least the first alert switch further comprises:

at least a first pushbutton switch adapted to generate the at least the first electrical alert actuation signal responsive to the at least the first pushbutton switch being manually actuated by the first diver;

a first transmitter electrically coupled to the at least the first alert switch and adapted to generate at least a first predetermined electrical transmit signal responsive to receiving the at least the first electrical alert actuation signal, respectively;

a first transmitting element electrically coupled to the first transmitter and adapted to generate at least a first predetermined wireless signal responsive to receiving the at least the first predetermined electrical transmit signal, respectively;

a first power supply adapted to provide a first supply of electrical power;

a first power switch adapted to electrically couple the first supply of electrical power to at least one of the at least the first alert switch, the first transmitter and the first transmitting element responsive to the first power switch being actuated; and

a first waterproof transmitter housing adapted to carry at least one of the at least the first alert switch, the first transmitter, the first transmitting element, the first power supply and the first power switch; and

a first receiver assembly, adapted to be carried by a second diver having a first mask adapted to be worn on the second diver's head, including:

a first receiving element adapted to generate at least a first electrical receive signal responsive to receiving the at least the first predetermined wireless signal, respectively;

a first receiver electrically coupled to the first receiving element and adapted to generate at least a first predetermined electrical alert attention signal responsive to receiving the at least the first electrical receive signal, respectively;

at least a first alert device electrically coupled to the first receiver and adapted to generate at least a first predetermined alert responsive to receiving the at least the first predetermined electrical alert attention signal, wherein the at least the first alert device further comprises:

a first visual alert device adapted to generate a first predetermined visual alert, as the at least the first predetermined alert, that the second diver can see when wearing the first mask, wherein the first visual alert device further comprises:

5 a first light source adapted to generate a first predetermined visible light signal, as the first predetermined visual alert;

a second power supply adapted to provide a second supply of electrical power;

a second power switch adapted to electrically couple the second supply of electrical power to at least one of the first receiving element, the first receiver and the at least the first alert device responsive to the second power switch being actuated; and

10 a first waterproof receiver housing adapted to carry at least one of the first receiving element, the first receiver, the at least the first alert device, the second power supply and the second power switch;

wherein the first mask is adapted to carry at least the at least the first alert device of the first receiver assembly in a way that permits the at least the first predetermined alert to gain the attention of the second diver when the first mask is worn on the second diver's head; and

15 a first attachment mechanism adapted to permit the first waterproof receiver housing to be mechanically coupled to the first mask.

2430. (Currently Amended) The underwater alert system according to claim 23—29 further comprising:

20 a second transmitter assembly, adapted to be carried by the second diver, including:

at least a second alert switch adapted to generate at least a second electrical alert actuation signal responsive to the at least the second alert switch being actuated, wherein the at least the second alert switch further comprises:

25 at least a second pushbutton switch adapted to generate the at least the second electrical alert actuation signal responsive to the at least the second pushbutton switch being manually actuated by the second diver;

a second transmitter electrically coupled to the at least the second alert switch and adapted to generate at least a second predetermined electrical transmit signal responsive to receiving the at least the second electrical alert actuation signal, respectively;

a second transmitting element electrically coupled to the second transmitter and adapted to generate at least a second predetermined wireless signal responsive to receiving the at least the second predetermined electrical transmit signal, respectively;

a third power supply adapted to provide a third supply of electrical power;

5 a third power switch adapted to electrically couple the second supply of electrical power to at least one of the at least the second alert switch, the second transmitter and the second transmitting element responsive to the third power switch being actuated; and

10 a second waterproof transmitter housing adapted to carry at least one of the at least the second alert switch, the second transmitter, the second transmitting element, the third power supply and the third power switch;

a second receiver assembly, adapted to be carried by the first diver having a second mask adapted to be worn on the first diver's head, including:

a second receiving element adapted to generate at least a second electrical receive signal responsive to receiving the at least the second predetermined wireless signal, respectively;

15 a second receiver electrically coupled to the second receiving element and adapted to generate at least a second predetermined electrical alert attention signal responsive to receiving the at least the second electrical receive signal, respectively;

20 at least a second alert device electrically coupled to the second receiver and adapted to generate at least a second predetermined alert responsive to receiving the at least the second predetermined electrical alert attention signal, wherein the at least the second alert device further comprises:

a second visual alert device adapted to generate a predetermined visual alert, as the at least the second predetermined alert, that the first diver can see when wearing the second mask, wherein the second visual alert device further comprises:

25 a second light source adapted to generate a second predetermined visible light signal, as the second predetermined visual alert;

a fourth power supply adapted to provide a fourth supply of electrical power;

30 a fourth power switch adapted to electrically couple the fourth supply of electrical power to at least one of the second receiving element, the second receiver and the at least the second alert device responsive to the fourth power switch being actuated; and

a second waterproof receiver housing adapted to carry at least one of the second receiving element, the second receiver, the at least the second alert device, the fourth power supply and the fourth power switch;

wherein the second mask is adapted to carry at least the at least the second alert device of the second receiver assembly in a way that permits the at least the second predetermined alert to gain the attention of the first diver when the second mask is worn on the first diver's head; and

a second attachment mechanism adapted to permit the second waterproof receiver housing to be mechanically coupled to the second mask.

~~2531.~~ (Currently Amended) The underwater alert system according to claim ~~2430~~,

wherein the first waterproof transmitter housing and the second waterproof receiver housing are integrally formed together to provide a first transceiver housing adapted to be carried by the second mask,

wherein the first power supply and the fourth power supply are integrally formed together to provide a first transceiver power supply adapted to be carried by the first transceiver housing;

wherein the first power switch and the fourth power switch are integrally formed together to provide a first transceiver power switch adapted to be carried by the first transceiver housing;

wherein the second waterproof transmitter housing and the first waterproof receiver housing are integrally formed together to provide a second transceiver housing adapted to be carried by the first mask;

wherein the second power supply and the third power supply are integrally formed together to provide a second transceiver power supply adapted to be carried by the second transceiver housing; and

wherein the second power switch and the third power switch are integrally formed together to provide a second transceiver power switch adapted to be carried by the second transceiver housing.

~~2632.~~ (Currently Amended) The underwater alert system according to claim ~~2531~~,

wherein the first transceiver housing is integrally formed with the second mask, and

wherein the second transceiver housing is integrally formed with the first mask.

2733. (Currently Amended) The underwater alert system according to claim 23-29, wherein the first attachment mechanism further comprises:

5 a first bracket adapted to be carried by the first mask and having a first mounting interface adapted to mechanically engage and disengage a first mounting interface on the first waterproof receiver housing to permit the first waterproof receiver housing to be attached to and removed from, respectively, the first bracket.

2834. (Currently Amended) The underwater alert system according to claim 27-33, wherein the first bracket further comprises:

10 a second mounting interface having an adhesive disposed thereon to permit the second mounting interface of the first bracket to be mechanically coupled to the first mask.

2935. (Currently Amended) The underwater alert system according to claim 27-33, wherein the first bracket is integrally formed with the first mask.

15 3036. (Currently Amended) The underwater alert system according to claim 23-29, wherein the first light source generates the first predetermined visible light signal when the first waterproof receiver housing is mechanically coupled to the first mask, and wherein a second alert device generates a second predetermined alert when the first waterproof receiver housing is mechanically
20 decoupled from the first mask.

3137. (Currently Amended) The underwater alert system according to claim 2329:

wherein the first transmitter assembly further comprises a first transmitter identity selection device adapted to provide the first transmitter with at least a first transmitter identity, and

25 wherein the first receiver assembly further comprises a first receiver identity selection device adapted to provide the first receiver with the at least the first transmitter identity to permit the first receiver to communicate with the first transmitter.

3238. (Currently Amended) The underwater alert system according to claim 23-29, wherein at least one of the first power switch and the second power switch further comprises:

a water-activated switch adapted to be actuated responsive to the water-activated switch being located underwater.

3339. (Currently Amended) The underwater alert system according to claim 23-29, further comprising:

a dive computer adapted to generate dive computer data, electrically coupled to the first transmitter, and adapted to be carried by the first diver,

wherein the at least the first alert switch further comprises:

an electronic switch electrically coupled to the dive computer and adapted to generate the at least the first electrical alert actuation signal responsive to the dive computer data being an undesirable, predetermined value.

3440. (Currently Amended) The underwater alert system according to claim 23-29, further comprising:

a dive computer adapted to generate dive computer data, electrically coupled to the first transmitter, and adapted to be carried by the first diver,

wherein the first transmitter is adapted to transmit dive computer data, associated with the dive computer, to the first receiver.

8941. (Represented - formerly dependent claim # 89) The underwater alert system according to claim 23-29, wherein the first transmitter assembly further comprises:

a light source carried by the first transmitter housing and adapted to illuminate at least a portion of the pushbutton.

9042. (Represented - formerly dependent claim # 90) The underwater alert system according to claim 23-29, wherein the first transmitter assembly further comprises:

a transmitter alert device adapted to generate at least a second predetermined alert responsive to a function of the first transmitter assembly.

9143. (Represented - formerly dependent claim # 91) The underwater alert system according to claim ~~90-42~~, wherein the function of the first transmitter assembly further comprises at least one of:

5 a low voltage warning, a verification of operation, a confirmation of transmitter identity selection, a confirmation of activation of the first alert switch, a confirmation of activation of the power on/off switch, and a condition of the charging circuit.

9244. (Represented - formerly dependent claim # 92) The underwater alert system according to claim ~~90-42~~, wherein the transmitter alert device further comprises at least one of:

10 a visual alert device adapted to generate a predetermined visual alert, as the at least the second predetermined alert, that the first diver can see when wearing the first transmitter assembly;

an audible alert device adapted to generate a predetermined audible alert, as the at least the second predetermined alert, that the first diver can hear when wearing the first transmitter assembly; and

15 a tactile alert device adapted to generate a predetermined tactile alert, as the at least the second predetermined alert, that the first diver can feel when wearing the first transmitter assembly.

9345. (Represented - formerly dependent claim # 93) The underwater alert system according to claim ~~23-29~~, wherein the at least the first alert switch is automatically actuated responsive to information related to at least one of the first diver's body, equipment and environment.

20 9446. (Represented - formerly dependent claim # 94) The underwater alert system according to claim ~~23-29~~, wherein the at least the first alert device generates the first predetermined alert when the first waterproof receiver housing is above water, and wherein the at least the first alert device generates a second predetermined alert when the first waterproof receiver housing is underwater.

3547. (Currently Amended) An underwater alert system comprising:

a first transmitter assembly, adapted to be carried by a first diver, including:

at least a first alert switch adapted to generate at least a first electrical alert actuation signal responsive to the at least the first alert switch being actuated;

5 a first transmitter electrically coupled to the at least the first alert switch and adapted to generate at least a first predetermined electrical transmit signal responsive to receiving the at least the first electrical alert actuation signal, respectively;

a first transmitting element electrically coupled to the first transmitter and adapted to generate at least a first predetermined wireless signal responsive to receiving the at least the first
10 predetermined electrical transmit signal, respectively;

a first waterproof transmitter housing adapted to carry at least one of the at least the first alert switch, the first transmitter and the first transmitting element;

a first receiver assembly, adapted to be carried by a second diver, including:

a first receiving element adapted to generate at least a first electrical receive signal
15 responsive to receiving the at least the first predetermined wireless signal, respectively;

a first receiver electrically coupled to the first receiving element and adapted to generate at least a first predetermined electrical alert attention signal responsive to receiving the at least the first electrical receive signal, respectively;

at least a first alert device electrically coupled to the first receiver and adapted to generate
20 at least a first predetermined alert responsive to receiving the at least the first predetermined electrical alert attention signal;

a first waterproof receiver housing adapted to carry at least one of the first receiving element, the first receiver and the at least the first alert device; and

a first mask adapted to be worn on the second diver's head and adapted to carry at least the at
25 least the first alert device of the first receiver assembly in a way that permits the at least the first predetermined alert to gain the attention of the second diver when the first mask is worn on the second diver's head, wherein the first waterproof receiver housing is integrally formed with the first mask.

30

3648. (Currently Amended) The underwater alert system according to claim 35-47, wherein the at least the first alert switch further comprises:

at least a first pushbutton switch adapted to generate the at least the first electrical alert actuation signal responsive to the at least the first pushbutton switch being manually actuated by the first diver.

3749. (Currently Amended) The underwater alert system according to claim 35-47, wherein the at least the first alert device further comprises:

a visual alert device adapted to generate a predetermined visual alert, as the at least the first predetermined alert, that the second diver can see when wearing the first mask.

3850. (Currently Amended) The underwater alert system according to claim 37-49, wherein the visual alert device further comprises:

a first light source adapted to generate a predetermined visible light signal, as the predetermined visual alert.

3951. (Currently Amended) The underwater alert system according to claim 35-47, wherein the at least the first alert device further comprises:

an audible alert device adapted to generate a predetermined audible alert, as the at least the first predetermined alert, that the second diver can hear when wearing the first mask.

4052. (Currently Amended) The underwater alert system according to claim 39-51, wherein the audible alert device further comprises:

an electro-acoustic transducer adapted to generate a predetermined audible acoustic signal, as the predetermined audible alert.

4153. (Currently Amended) The underwater alert system according to claim 35-47, wherein the at least the first alert device further comprises:

a tactile alert device adapted to generate a predetermined tactile alert, as the at least the first predetermined alert, that the second diver can feel when wearing the first mask.

4254. (Currently Amended) The underwater alert system according to claim 41-53, wherein the tactile alert device further comprises:

a vibrator adapted to generate a predetermined vibration signal, as the predetermined tactile alert.

5

4355. (Currently Amended) The underwater alert system according to claim 35-47 further comprising:

a second transmitter assembly adapted to be carried by the second diver and including:

at least a second alert switch adapted to generate at least a second electrical alert actuation signal responsive to the at least the second alert switch being actuated;

10

a second transmitter electrically coupled to the at least the second alert switch and adapted to generate at least a second predetermined electrical transmit signal responsive to receiving the at least the second electrical alert actuation signal, respectively;

a second transmitting element electrically coupled to the second transmitter and adapted to generate at least a second predetermined wireless signal responsive to receiving the at least the second predetermined electrical transmit signal, respectively; and

15

a second waterproof transmitter housing adapted to carry at least one of the at least the second alert switch, the second transmitter and the second transmitting element;

a second receiver assembly, adapted to be carried by the first diver, including:

a second receiving element adapted to generate at least a second electrical receive signal responsive to receiving the at least the second predetermined wireless signal, respectively;

20

a second receiver electrically coupled to the second receiving element and adapted to generate at least a second predetermined electrical alert attention signal responsive to receiving the at least the second electrical receive signal, respectively;

at least a second alert device electrically coupled to the second receiver and adapted to generate at least a second predetermined alert responsive to receiving the at least the second predetermined electrical alert attention signal; and

25

a second waterproof receiver housing adapted to carry at least one of the second receiving element, the second receiver and the at least the second alert device; and

a second mask adapted to be worn on the first diver's head and adapted to carry at least the at least the second alert device of the second receiver assembly in a way that permits the at least the

30

second predetermined alert to gain the attention of the first diver when the second mask is worn on the first diver's head, wherein the second waterproof receiver housing is integrally formed with the second mask.

5 ~~4456.~~ (Currently Amended) The underwater alert system according to claim ~~4355~~,₁

wherein the first waterproof transmitter housing and the second waterproof receiver housing are integrally formed with the second mask to provide a first transceiver housing, and

wherein the second waterproof transmitter housing and the first waterproof receiver housing are integrally formed with the first mask to provide a second transceiver housing.

10

~~4557.~~ (Currently Amended) The underwater alert system according to claim ~~3547~~,₁

wherein the first transmitter assembly further comprises a first transmitter identity selection device adapted to provide the first transmitter with at least a first transmitter identity, and

wherein the first receiver assembly further comprises a first receiver identity selection device

15 adapted to provide the first receiver with the at least the first transmitter identity to permit the first receiver to communicate with the first transmitter.

~~4658.~~ (Currently Amended) The underwater alert system according to claim ~~3547~~,₁

wherein the first transmitter assembly further comprises:

20

a first power supply adapted to provide a first supply of electrical power; and

a first power switch adapted to electrically couple the first supply of electrical power to at

least one of the at least the first alert switch, the first transmitter and the first transmitting element responsive to the first power switch being actuated;₁ and

wherein the first receiver assembly further comprises:

25

a second power supply adapted to provide a second supply of electrical power; and

a second power switch adapted to electrically couple the second supply of electrical power to at least one of the first receiving element, the first receiver and the at least the first alert device responsive to the second power switch being actuated.

30

4759. (Currently Amended) The underwater alert system according to claim 46-58, wherein at least one of the first power switch and the second power switch further comprises:

a water-activated switch adapted to be actuated responsive to the water-activated switch being located underwater.

5

4860. (Currently Amended) The underwater alert system according to claim 35-47 further comprising:

a dive computer adapted to generate dive computer data, electrically coupled to the first transmitter, and adapted to be carried by the first diver,

10

wherein the at least the first alert switch further comprises:

an electronic switch electrically coupled to the dive computer and adapted to generate the at least the first electrical alert actuation signal responsive to the dive computer data being an undesirable, predetermined value.

15

4961. (Currently Amended) The underwater alert system according to claim 35-47 further comprising:

a dive computer adapted to generate dive computer data, electrically coupled to the first transmitter, and adapted to be carried by the first diver,

wherein the first transmitter is adapted to transmit dive computer data, associated with the dive computer, to the first receiver.

20

5062. (Currently Amended) In an underwater alert system including a first transmitter assembly adapted to be carried by a first diver and a first receiver assembly adapted to be carried by a second diver having a first mask adapted to be worn on the second diver's head, the first transmitter assembly comprising:

5 at least a first alert switch adapted to generate at least a first electrical alert actuation signal responsive to the at least the first alert switch being actuated;

a first transmitter electrically coupled to the at least the first alert switch and adapted to generate at least a first predetermined electrical transmit signal responsive to receiving the at least the first electrical alert actuation signal, respectively;

10 a first transmitting element electrically coupled to the first transmitter and adapted to generate at least a first predetermined wireless signal responsive to receiving the at least the first predetermined electrical transmit signal, respectively; and

a first waterproof transmitter housing adapted to carry at least one of the at least the first alert switch, the first transmitter and the first transmitting element;

15 wherein the first receiver assembly includes:

a first receiving element adapted to generate at least a first electrical receive signal responsive to receiving the at least the first predetermined wireless signal, respectively;

20 a first receiver electrically coupled to the first receiving element and adapted to generate at least a first predetermined electrical alert attention signal responsive to receiving the at least the first electrical receive signal, respectively;

at least a first alert device electrically coupled to the first receiver and adapted to generate at least a first predetermined alert responsive to receiving the at least the first predetermined electrical alert attention signal; and

25 a first waterproof receiver housing adapted to carry at least one of the first receiving element, the first receiver and the at least the first alert device;

wherein the first mask is adapted to carry at least the at least the first alert device of the first receiver assembly in a way that permits the at least the first predetermined alert to gain the attention of the second diver when the first mask is worn on the second diver's head.

5 ~~5163.~~ (Currently Amended) The first transmitter assembly according to claim ~~5062~~, wherein the at least the first alert switch further comprises:

at least a first pushbutton switch adapted to generate the at least the first electrical alert actuation signal responsive to the at least the first pushbutton switch being manually actuated by the first diver.

10 ~~5264.~~ (Currently Amended) The first transmitter assembly according to claim ~~5062~~:

wherein the first diver has a second mask adapted to be worn on the first diver's head, and wherein the first waterproof transmitter housing is adapted to be carried by the second mask.

15 ~~5365.~~ (Currently Amended) The first transmitter assembly according to claim ~~5264~~:

wherein the first waterproof transmitter housing is integrally formed with the second mask.

20 ~~5466.~~ (Currently Amended) The first transmitter assembly ~~The underwater alert system~~ according to claim ~~5062~~:

~~wherein the first transmitter assembly further comprises comprising:~~

~~a first transmitter identity selection device adapted to provide the first transmitter with at least a first transmitter identity, and~~

wherein the first receiver assembly further comprises a first receiver identity selection device adapted to provide the first receiver with the at least the first transmitter identity to permit the first receiver to communicate with the first transmitter.

25 ~~5567.~~ (Currently Amended) The first transmitter assembly ~~The underwater alert system~~ according to claim ~~5062~~:

~~wherein the first transmitter assembly further comprises:~~

~~—a first power supply adapted to provide a first supply of electrical power; and~~

~~—a first power switch adapted to electrically couple the first supply of electrical power to at least one of the at least the first alert switch, the first transmitter and the first transmitting element responsive to the first power switch being actuated; and~~

30 ~~wherein the first receiver assembly further comprises:~~

~~—a second power supply adapted to provide a second supply of electrical power; and~~

~~_____ a second power switch adapted to electrically couple the second supply of electrical power to at least one of the first receiving element, the first receiver and the at least the first alert device responsive to the second power switch being actuated.~~

- 5 5668. (Currently Amended) The first transmitter assembly ~~The underwater alert system~~ according to claim ~~55-67~~, wherein at least one of the first power switch and the second power switch further comprises:

 a water-activated switch adapted to be actuated responsive to the water-activated switch being located underwater.

10

5769. (Currently Amended) The first transmitter assembly ~~The underwater alert system~~ according to claim ~~50-62~~ further comprising:

 a dive computer adapted to generate dive computer data, electrically coupled to the first transmitter, and adapted to be carried by the first diver,

15

 wherein the at least the first alert switch further comprises:

 an electronic switch electrically coupled to the dive computer and adapted to generate the at least the first electrical alert actuation signal responsive to the dive computer data being an undesirable, predetermined value.

20

5870. (Currently Amended) The first transmitter assembly ~~The underwater alert system~~ according to claim ~~50-62~~ further comprising:

~~a dive computer adapted to generate dive computer data, electrically coupled to the first transmitter, and adapted to be carried by the first diver,~~

25

 wherein the first transmitter is adapted to transmit dive computer data, associated with the dive computer, to the first receiver.

9771. (Represented - formerly dependent claim # 97) The first transmitter assembly ~~The underwater alert system~~ according to claim ~~50-62~~ wherein the first transmitter assembly further comprises:

30

 a light source carried by the first transmitter housing and adapted to illuminate at least a portion of the pushbutton.

9872. (Represented - formerly dependent claim # 98) The first transmitter assembly ~~The underwater alert system~~ according to claim 50-62 wherein the first transmitter assembly further comprises:

5 a transmitter alert device adapted to generate at least a second predetermined alert responsive to a function of the first transmitter assembly.

9973. (Represented - formerly dependent claim # 99) The first transmitter assembly ~~The underwater alert system~~ according to claim 98-72, wherein the function of the first transmitter
10 assembly further comprises at least one of:

a low voltage warning, a verification of operation, a confirmation of transmitter identity selection, a confirmation of activation of the first alert switch, a confirmation of activation of the power on/off switch, and a condition of the charging circuit.

15 10074. (Represented - formerly dependent claim # 100) The first transmitter assembly ~~The underwater alert system~~ according to claim 98-72, wherein the transmitter alert device further comprises at least one of:

a visual alert device adapted to generate a predetermined visual alert, as the at least the second predetermined alert, that the first diver can see when wearing the first transmitter assembly;

20 an audible alert device adapted to generate a predetermined audible alert, as the at least the second predetermined alert, that the first diver can hear when wearing the first transmitter assembly;
and

a tactile alert device adapted to generate a predetermined tactile alert, as the at least the second predetermined alert, that the first diver can feel when wearing the first transmitter assembly.

25 10175. (Represented - formerly dependent claim # 101) The first transmitter assembly ~~The underwater alert system~~ according to claim 50-62, wherein the at least the first alert switch is automatically actuated responsive to information related to at least one of the first diver's body, equipment and environment.

30

~~59~~76. (Currently Amended) In an underwater alert system including a first transmitter assembly adapted to be carried by a first diver and a first receiver assembly adapted to be carried by a second diver having a first mask adapted to be worn on the second diver's head, the first receiver assembly comprising:

5 a first receiving element adapted to generate at least a first electrical receive signal responsive to receiving at least a first predetermined wireless signal, respectively, generated by the first transmitter assembly;

 a first receiver electrically coupled to the first receiving element and adapted to generate at least a first predetermined electrical alert attention signal responsive to receiving the at least the first
10 electrical receive signal, respectively;

 at least a first alert device electrically coupled to the first receiver and adapted to generate at least a first predetermined alert responsive to receiving the at least the first predetermined electrical alert attention signal; and

 a first waterproof receiver housing adapted to carry at least one of the first receiving element,
15 the first receiver and the at least the first alert device,

 wherein the first mask is adapted to carry at least the at least the first alert device of the first receiver assembly in a way that permits the at least the first predetermined alert to gain the attention of the second diver when the first mask is worn on the second diver's head.

20 ~~60~~77. (Currently Amended) The first receiver assembly according to claim ~~59-76~~, wherein the at least the first alert device further comprises:

 a visual alert device adapted to generate a predetermined visual alert, as the at least the first predetermined alert, that the second diver can see when wearing the first mask.

25 ~~64~~78. (Currently Amended) The first receiver assembly according to claim ~~60-77~~, wherein the visual alert device further comprises:

 a first light source adapted to generate a predetermined visible light signal, as the predetermined visual alert.

30

6279. (Currently Amended) The first receiver assembly according to claim ~~59-76~~, wherein the at least the first alert device further comprises:

an audible alert device adapted to generate a predetermined audible alert, as the at least the first predetermined alert, that the second diver can hear when wearing the first mask.

5 6380. (Currently Amended) The first receiver assembly according to claim ~~62-79~~, wherein the audible alert device further comprises:

an electro-acoustic transducer adapted to generate a predetermined audible acoustic signal, as the predetermined audible alert.

10 6481. (Currently Amended) The first receiver assembly according to claim ~~59-76~~, wherein the at least the first alert device further comprises:

a tactile alert device adapted to generate a predetermined tactile alert, as the at least the first predetermined alert, that the second diver can feel when wearing the first mask.

15 6582. (Currently Amended) The first receiver assembly according to claim ~~64-81~~, wherein the tactile alert device further comprises:

a vibrator adapted to generate a predetermined vibration signal, as the predetermined tactile alert.

20 6683. (Currently Amended) The first receiver assembly according to claim ~~59-76~~, further comprising:

a first attachment mechanism adapted to permit the first waterproof receiver housing to be mechanically coupled to the first mask.

25 6784. (Currently Amended) The first receiver assembly according to claim ~~66-83~~, wherein the first attachment mechanism further comprises:

30 a first bracket adapted to be carried by the first mask and having a first mounting interface adapted to mechanically engage and disengage a first mounting interface on the first waterproof receiver housing to permit the first waterproof receiver housing to be attached to and removed from, respectively, the first bracket.

6885. (Currently Amended) The first receiver assembly according to claim ~~67-84~~, wherein the first bracket further comprises:

5 a second mounting interface having an adhesive disposed thereon to permit the second mounting interface of the first bracket to be mechanically coupled to the first mask.

6986. (Currently Amended) The first receiver assembly according to claim ~~67-84~~, wherein the first bracket is integrally formed with the first mask.

10 7087. (Currently Amended) The first receiver assembly according to claim ~~66-83~~, wherein the at least the first alert device generates the first predetermined alert when the first waterproof receiver housing is mechanically coupled to the first mask, and wherein the at least the first alert device generates a second predetermined alert when the first waterproof receiver housing is mechanically decoupled from the first mask.

15 7188. (Currently Amended) The first receiver assembly according to claim ~~59-76~~, wherein the first waterproof receiver housing is integrally formed with the first mask.

20 7289. (Currently Amended) The first receiver assembly according to claim ~~59-76~~, wherein the first receiver assembly further comprises a first receiver identity selection device adapted to provide the first receiver with the at least the first transmitter identity, associated with the first transmitter, to permit the first receiver to communicate with the first transmitter.

25 7390. (Currently Amended) The first receiver assembly according to claim ~~59-76~~, further comprising:

a second power supply adapted to provide a second supply of electrical power; and

a second power switch adapted to electrically couple the second supply of electrical power to at least one of the first receiving element, the first receiver and the at least the first alert device responsive to the second power switch being actuated.

7491. (Currently Amended) The first receiver assembly ~~The underwater alert system~~ according to claim 73-90, wherein the second power switch further comprises:

a water-activated switch adapted to be actuated responsive to the water-activated switch being located underwater.

7592. (Currently Amended) The first receiver assembly ~~The underwater alert system~~ according to claim 59-76, wherein the first predetermined electrical alert attention signal is representative of dive computer data, having an undesirable, predetermined value, associated with a dive computer, electrically coupled to the first transmitter assembly and adapted to be carried by the first diver.

7693. (Currently Amended) The first receiver assembly ~~The underwater alert system~~ according to claim 59-76, wherein the first receiver is adapted to receive dive computer data associated with a dive computer, electrically coupled to the first transmitter assembly and adapted to be carried by the first diver.

10294. (Represented - formerly dependent claim # 102) The first receiver assembly ~~The underwater alert system~~ according to claim 59-76, wherein the at least the first alert device generates the first predetermined alert when the first waterproof receiver housing is above water, and wherein the at least the first alert device generates a second predetermined alert when the first waterproof receiver housing is underwater.

~~7795~~. (Currently Amended) In an underwater alert system including a first transmitter assembly adapted to be carried by a first diver, a first receiver assembly adapted to be carried by a second diver and a mask adapted to be worn on the second diver's head, the mask comprising:

5 a first receiving element adapted to generate at least a first electrical receive signal responsive to receiving at least a first predetermined wireless signal, respectively, generated by the first transmitter assembly;

a first receiver electrically coupled to the first receiving element and adapted to generate at least a first predetermined electrical alert attention signal responsive to receiving the at least the first electrical receive signal, respectively;

10 at least a first alert device electrically coupled to the first receiver and adapted to generate at least a first predetermined alert responsive to receiving the at least the first predetermined electrical alert attention signal; and

a first waterproof receiver housing adapted to carry at least one of the first receiving element, the first receiver and the at least the first alert device,

15 wherein at least the at least the first alert device of the first receiver assembly is carried on the mask in a way that permits the at least the first predetermined alert to gain the attention of the second diver when the mask is worn on the second diver's head.

7896. (Currently Amended) An underwater alert system comprising:

means for providing a first transmitter assembly, adapted to be carried by a first diver, including:

means for generating at least a first electrical alert actuation signal;

5 means for generating at least a first predetermined electrical transmit signal responsive to receiving the at least the first electrical alert actuation signal, respectively;

means for generating at least a first predetermined wireless signal responsive to receiving the at least the first predetermined electrical transmit signal, respectively; and

10 means for carrying at least one of the means for generating the at least a first electrical alert actuation signal, the means for generating the at least the first predetermined electrical transmit signal, and the means for generating the at least the first predetermined wireless signal; and

means for providing a receiver assembly, adapted to be carried by a second diver having an mask adapted to be worn on the second diver's head, including:

15 means for generating at least a first electrical receive signal responsive to receiving the at least the first predetermined wireless signal, respectively;

means for generating at least a first predetermined electrical alert attention signal responsive to receiving the at least the first electrical receive signal, respectively;

means for generating at least a first predetermined alert responsive to receiving the at least the first predetermined electrical alert attention signal; and

20 means for carrying at least one of the means for generating the at least the first electrical receive signal, the means for generating the at least the first predetermined electrical alert attention signal, and the means for generating the at least the first predetermined alert;—

25 wherein the first mask is adapted to carry at least the at least the means for generating the at least the first predetermined alert in a way that permits the at least the first predetermined alert to gain the attention of the second diver when the first mask is worn on the second diver's head.

Claims 79 – 102 (Cancelled).

13097. (Represented – formerly independent claim # 130) An underwater alert system comprising:

a first transmitter assembly, adapted to be carried by a first ~~person~~ diver while the first diver ~~person~~ is underwater, for transmitting a first predetermined wireless signal; and

a first receiver assembly, adapted to be carried by a second diver ~~person~~ while the second diver ~~person~~ is underwater, including:

~~an~~ a first alert device, adapted to be carried by a first mask to be worn on the second diver's head, for generating ~~an~~ a first predetermined alert that gains the attention of the second diver when the first mask is worn on the second diver's head responsive to receiving the first predetermined wireless signal.

98. (New) The underwater alert system according to claim 97, wherein the at least the first transmitter assembly further comprises:

a pushbutton switch adapted to generate the an electrical alert actuation signal responsive to the pushbutton switch being manually actuated by the first diver.

99. (New) The underwater alert system according to claim 97, wherein the first alert device further comprises:

a visual alert device adapted to generate a predetermined visual alert, as the first predetermined alert, which the second diver can see when wearing the first mask.

100. (New) The underwater alert system according to claim 97, wherein the first alert device further comprises:

an audible alert device adapted to generate a predetermined audible alert, as the first predetermined alert, which the second diver can hear when wearing the first mask.

101. (New) The underwater alert system according to claim 97, wherein the first alert device further comprises:

a tactile alert device adapted to generate a predetermined tactile alert, as the first predetermined alert, which the second diver can feel when wearing the first mask.

102. (New) The underwater alert system according to claim 97, further comprising:

a second transmitter assembly, adapted to be carried by the second diver while the second diver is underwater, for transmitting a second predetermined wireless signal; and

a second receiver assembly, adapted to be carried by the first diver while the first diver is underwater, including:

a second alert device, adapted to be carried by a second mask to be worn on the first diver's head, for generating a second predetermined alert that gains the attention of the first diver when the second mask is worn on the first diver's head responsive to receiving the second predetermined wireless signal.

103. (New) The underwater alert system according to claim 97, further comprising:

a first attachment mechanism adapted to permit the first receiver assembly to be mechanically coupled to the first mask.

104. (New) The underwater alert system according to claim 103, wherein the first alert device generates the first predetermined alert when the first receiver assembly is mechanically coupled to the first mask; and wherein the first alert device generates a second predetermined alert when the first receiver assembly is mechanically decoupled from the first mask.

105. (New) The underwater alert system according to claim 97, wherein the first receiver assembly is integrally formed with the first mask.

106. (New) The underwater alert system according to claim 97,

wherein the first transmitter assembly further comprises a first transmitter identity selection device adapted to provide the first transmitter assembly with at least a first transmitter identity, and wherein the first receiver assembly further comprises a first receiver identity selection device adapted to provide the first receiver assembly with the at least the first transmitter identity to permit the first receiver assembly to communicate with the first transmitter assembly.

107. (New) The underwater alert system according to claim 97,

wherein the first transmitter assembly further comprises:

a first power supply adapted to provide a first supply of electrical power; and

a first power switch adapted to electrically couple the first supply of electrical power to at

5 least one of the at least the first alert switch, the first transmitter and the first transmitting element responsive to the first power switch being actuated, and

wherein the first receiver assembly further comprises:

a second power supply adapted to provide a second supply of electrical power; and

10 a second power switch adapted to electrically couple the second supply of electrical power to at least one of the first receiving element, the first receiver and the at least the first alert device responsive to the second power switch being actuated.

108. (New) The underwater alert system according to claim 97 further comprising:

15 a dive computer adapted to generate dive computer data, electrically coupled to the first transmitter, and adapted to be carried by the first diver,

wherein the at least the first alert switch further comprises:

an electronic switch electrically coupled to the dive computer and adapted to generate the at least the first electrical alert actuation signal responsive to the dive computer data being an undesirable, predetermined value.

20 109. (New) The underwater alert system according to claim 97 further comprising:

a dive computer adapted to generate dive computer data, electrically coupled to the first transmitter, and adapted to be carried by the first diver,

25 wherein the first transmitter is adapted to transmit dive computer data, associated with the dive computer, to the first receiver.

110. (New) The underwater alert system according to claim 97, wherein the first transmitter assembly further comprises:

30 a transmitter alert device adapted to generate at least a second predetermined alert responsive to a function of the first transmitter assembly.

111. (New) The underwater alert system according to claim 97, wherein the first predetermined wireless signal is automatically transmitted responsive to information related to at least one of the first diver's body, equipment and environment.

5 112. (New) The underwater alert system according to claim 97, wherein the first alert device generates the first predetermined alert when the first receiver assembly is above water, and wherein the first alert device generates a second predetermined alert when the first receiver assembly is underwater.

10 113. (New) The underwater alert system according to any one of the preceding one hundred twelve claims numbered 1 to 112, wherein the first transmitter assembly further comprises:

15 a second attachment mechanism adapted to permit the first transmitter assembly to be mechanically coupled to the first diver's body or to equipment worn on the first diver's body at a location disposed below the first diver's head relative to the first diver being in an upright, standing position.

114. (New) The underwater alert system according to claim 113, wherein the second attachment mechanism further comprises at least one of:

a wristband, a strap, a cord, a band, a belt, a clip, and a clamp.

20

403115. (Currently Amended) An underwater alert system comprising:

a first transmitter assembly, adapted to be carried by a first diver, including:

at least a first alert switch adapted to generate at least a first electrical alert actuation signal responsive to the at least the first alert switch being actuated, wherein the at least the first alert switch further comprises:

at least a first pushbutton switch adapted to generate the at least the first electrical alert actuation signal responsive to the at least the first pushbutton switch being manually actuated by the first diver;

a first transmitter electrically coupled to the at least the first alert switch and adapted to generate at least a first predetermined electrical transmit signal responsive to receiving the at least the first electrical alert actuation signal, respectively;

a first transmitting element electrically coupled to the first transmitter and adapted to generate at least a first predetermined wireless signal responsive to receiving the at least the first predetermined electrical transmit signal, respectively;

a first waterproof transmitter housing adapted to carry at least one of the at least the first alert switch, the first transmitter and the first transmitting element; and

a second attachment mechanism adapted to permit the first waterproof transmitter housing to be mechanically coupled to the first diver's body to the first diver being in an upright, standing position, wherein the second attachment mechanism or to equipment worn on the first diver's body at a location disposed below the first diver's head relative further comprises at least one of:

a wristband, a strap, a cord, a band, a belt, a clip, and a clamp; and

a first receiver assembly, adapted to be carried by a second diver having a first mask adapted to be worn on the second diver's head, including:

a first receiving element adapted to generate at least a first electrical receive signal responsive to receiving the at least the first predetermined wireless signal, respectively;

a first receiver electrically coupled to the first receiving element and adapted to generate at least a first predetermined electrical alert attention signal responsive to receiving the at least the first electrical receive signal, respectively;

at least a first alert device electrically coupled to the first receiver and adapted to generate at least a first predetermined alert responsive to receiving the at least the first predetermined electrical alert attention signal; and

a first waterproof receiver housing adapted to carry at least one of the first receiving element, the first receiver and the at least the first alert device;

wherein the first mask is adapted to carry at least the at least the first alert device of the first receiver assembly in a way that permits the at least the first predetermined alert to gain the attention of the second diver when the first mask is worn on the second diver's head.

10 ~~404~~116. (Currently Amended) The underwater alert system according to claim ~~403-115~~, wherein the at least the first alert device further comprises:

a visual alert device adapted to generate a predetermined visual alert, as the at least the first predetermined alert, that the second diver can see when wearing the first mask.

15 ~~405~~117. (Currently Amended) The underwater alert system according to claim ~~404-116~~, wherein the visual alert device further comprises:

a first light source adapted to generate a predetermined visible light signal, as the predetermined visual alert.

20 ~~406~~118. (Currently Amended) The underwater alert system according to claim ~~403-115~~, wherein the at least the first alert device further comprises:

an audible alert device adapted to generate a predetermined audible alert, as the at least the first predetermined alert, that the second diver can hear when wearing the first mask.

25 ~~407~~119. (Currently Amended) The underwater alert system according to claim ~~406-118~~, wherein the audible alert device further comprises:

an electro-acoustic transducer adapted to generate a predetermined audible acoustic signal, as the predetermined audible alert.

30

~~408~~120. (Currently Amended) The underwater alert system according to claim ~~403-115~~, wherein the at least the first alert device further comprises:

a tactile alert device adapted to generate a predetermined tactile alert, as the at least the first predetermined alert, that the second diver can feel when wearing the first mask.

~~409~~121. (Currently Amended) The underwater alert system according to claim ~~408-120~~, wherein the tactile alert device further comprises:

a vibrator adapted to generate a predetermined vibration signal, as the predetermined tactile alert.

~~410~~122. (Currently Amended) The underwater alert system according to claim ~~403-115~~, further comprising:

a second transmitter assembly adapted to be carried by the second diver and including:

at least a second alert switch adapted to generate at least a second electrical alert actuation signal responsive to the at least the second alert switch being actuated, wherein the at least the second alert switch further comprises:

at least a second pushbutton switch adapted to generate the at least the second electrical alert actuation signal responsive to the at least the second pushbutton switch being manually actuated by the second diver;

a second transmitter electrically coupled to the at least the second alert switch and adapted to generate at least a second predetermined electrical transmit signal responsive to receiving the at least the second electrical alert actuation signal, respectively;

a second transmitting element electrically coupled to the second transmitter and adapted to generate at least a second predetermined wireless signal responsive to receiving the at least the second predetermined electrical transmit signal, respectively;

a second waterproof transmitter housing adapted to carry at least one of the at least the second alert switch, the second transmitter and the second transmitting element; and

a second attachment mechanism adapted to permit the second waterproof transmitter housing to be mechanically coupled to the second diver's body or to equipment worn on the second diver's body at a location disposed below the second diver's head relative to the second diver being

in an upright, standing position, wherein the second attachment mechanism further comprises at least one of:

a wristband, a strap, a cord, a band, a belt, a clip, and a clamp; and

a second receiver assembly, adapted to be carried by the first diver having a second mask

5 adapted to be worn on the first diver's head, including:

a second receiving element adapted to generate at least a second electrical receive signal responsive to receiving the at least the second predetermined wireless signal, respectively;

a second receiver electrically coupled to the second receiving element and adapted to generate at least a second predetermined electrical alert attention signal responsive to receiving the
10 at least the second electrical receive signal, respectively;

at least a second alert device electrically coupled to the second receiver and adapted to generate at least a second predetermined alert responsive to receiving the at least the second predetermined electrical alert attention signal; and

a second waterproof receiver housing adapted to carry at least one of the second
15 receiving element, the second receiver and the at least the second alert device; and

wherein the second mask is adapted to carry at least the at least the second alert device of the second receiver assembly in a way that permits the at least the second predetermined alert to gain the attention of the first diver when the second mask is worn on the first diver's head.

20 Claims 111-112 (Cancelled)

~~443123.~~ (Currently Amended) The underwater alert system according to claim ~~403-115~~, further comprising:

a first attachment mechanism adapted to permit the first waterproof receiver housing to be
25 mechanically coupled to the first mask.

~~444124.~~ (Currently Amended) The underwater alert system according to claim ~~443-123~~, wherein the first attachment mechanism further comprises:

a first bracket adapted to be carried by the first mask and having a first mounting interface
30 adapted to mechanically engage and disengage a first mounting interface on the first waterproof

receiver housing to permit the first waterproof receiver housing to be attached to and removed from, respectively, the first bracket.

5 ~~445~~125. (Currently Amended) The underwater alert system according to claim ~~444~~124, wherein the first bracket further comprises:

a second mounting interface having an adhesive disposed thereon to permit the second mounting interface of the first bracket to be mechanically coupled to the first mask.

10 ~~446~~126. (Currently Amended) The underwater alert system according to claim ~~444~~124, wherein the first bracket is integrally formed with the first mask.

~~447~~127. (Currently Amended) The underwater alert system according to claim ~~443~~123, wherein the at least the first alert device generates the first predetermined alert when the first waterproof receiver housing is mechanically coupled to the first mask, and wherein the at least the first alert
15 device generates a second predetermined alert when the first waterproof receiver housing is mechanically decoupled from the first mask.

~~448~~128. (Currently Amended) The underwater alert system according to claim ~~403~~115, wherein the first waterproof receiver housing is integrally formed with the first mask.

20

~~449~~129. (Currently Amended) The underwater alert system according to claim ~~403~~115, wherein the first transmitter assembly further comprises a first transmitter identity selection

device adapted to provide the first transmitter with at least a first transmitter identity, and

wherein the first receiver assembly further comprises a first receiver identity selection device
25 adapted to provide the first receiver with the at least the first transmitter identity to permit the first receiver to communicate with the first transmitter.

30

~~420~~130. (Currently Amended) The underwater alert system according to claim ~~403~~115,

wherein the first transmitter assembly further comprises:

a first power supply adapted to provide a first supply of electrical power; and

a first power switch adapted to electrically couple the first supply of electrical power to at

5 least one of the at least the first alert switch, the first transmitter and the first transmitting element responsive to the first power switch being actuated; and

wherein the first receiver assembly further comprises:

a second power supply adapted to provide a second supply of electrical power; and

10 a second power switch adapted to electrically couple the second supply of electrical power to at least one of the first receiving element, the first receiver and the at least the first alert device responsive to the second power switch being actuated.

~~421~~131. (Currently Amended) The underwater alert system according to claim ~~420~~130, wherein at least one of the first power switch and the second power switch further comprises:

15 a water-activated switch adapted to be actuated responsive to the water-activated switch being located underwater.

~~422~~132. (Currently Amended) The underwater alert system according to claim ~~403~~115 further comprising:

20 a dive computer adapted to generate dive computer data, electrically coupled to the first transmitter, and adapted to be carried by the first diver,

wherein the at least the first alert switch further comprises:

an electronic switch electrically coupled to the dive computer and adapted to generate the at least the first electrical alert actuation signal responsive to the dive computer data being an

25 undesirable, predetermined value.

~~423~~133. (Currently Amended) The underwater alert system according to claim ~~403-115~~ further comprising:

a dive computer adapted to generate dive computer data, electrically coupled to the first transmitter, and adapted to be carried by the first diver,

5 wherein the first transmitter is adapted to transmit dive computer data, associated with the dive computer, to the first receiver.

~~424~~134. (Currently Amended) The underwater alert system according to claim ~~403-115~~, wherein the first transmitter assembly further comprises:

10 a light source carried by the first transmitter housing and adapted to illuminate at least a portion of the pushbutton.

~~425~~135. (Currently Amended) The underwater alert system according to claim ~~403-115~~, wherein the first transmitter assembly further comprises:

15 a transmitter alert device adapted to generate at least a second predetermined alert responsive to a function of the first transmitter assembly.

~~426~~136. (Currently Amended) The underwater alert system according to claim ~~425-135~~, wherein the function of the first transmitter assembly further comprises at least one of:

20 a low voltage warning, a verification of operation, a confirmation of transmitter identity selection, a confirmation of activation of the first alert switch, a confirmation of activation of the power on/off switch, and a condition of the charging circuit.

25

30

~~427~~137. (Currently Amended) The underwater alert system according to claim ~~425-135~~, wherein the transmitter alert device further comprises at least one of:

a visual alert device adapted to generate a predetermined visual alert, as the at least the second predetermined alert, that the first diver can see when wearing the first transmitter assembly;

5 an audible alert device adapted to generate a predetermined audible alert, as the at least the second predetermined alert, that the first diver can hear when wearing the first transmitter assembly; and

a tactile alert device adapted to generate a predetermined tactile alert, as the at least the second predetermined alert, that the first diver can feel when wearing the first transmitter assembly.

10

~~428~~138. (Currently Amended) The underwater alert system according to claim ~~403-115~~, wherein the at least the first alert switch is automatically actuated responsive to information related to at least one of the first diver's body, equipment and environment.

15

~~429~~139. (Currently Amended) The underwater alert system according to claim ~~403-115~~, wherein the at least the first alert device generates the first predetermined alert when the first waterproof receiver housing is above water, and wherein the at least the first alert device generates a second predetermined alert when the first waterproof receiver housing is underwater.

433140. (Currently Amended) An underwater alert system comprising:

at least a one transmitter assembly, adapted to be carried by a first diver while the first diver is underwater, for transmitting at least one wireless signal responsive to receiving first dive computer data related to at least one of the first diver's body, equipment, and environment;

5 a first receiver assembly, adapted to be carried by a second diver while the second diver is underwater, for communicating to the second diver first information related to the first dive computer data responsive to receiving the at least one wireless signal over a first wireless communication link, having a first range, between the at least one transmitter assembly and the first receiver assembly; and

10 a second receiver assembly, adapted to be carried by the first diver while the first diver is underwater, for communicating to the first diver second information related to the first dive computer data responsive to receiving the at least one wireless signal over a second wireless communication link, having a second range, between the at least one transmitter assembly and the second receiver assembly.

15 a first transmitter assembly, adapted to be carried by a first diver, including:

—— a first dive computer adapted to generate first dive computer data responsive to receiving information related to at least one of the first diver's body, equipment, and environment;

20 —— a first transmitter electrically coupled to the first dive computer and adapted to generate at least a first electrical transmit signal responsive to receiving the first dive computer data, respectively;

—— a first transmitting element electrically coupled to the first transmitter and adapted to generate at least a first wireless signal responsive to receiving the at least the first electrical transmit signal, respectively; and

25 —— a first waterproof transmitter housing adapted to carry at least one of the first dive computer, the first transmitter and the first transmitting element; and

—— a first receiver assembly, adapted to be carried by a second diver, including:

—— a first receiving element adapted to generate at least a first electrical receive signal responsive to receiving the at least the first wireless signal, respectively;

30 —— a first receiver electrically coupled to the first receiving element and adapted to generate at least a first electrical alert attention signal responsive to receiving the at least the first electrical receive signal, respectively;

~~at least a first alert device electrically coupled to the first receiver and adapted to generate at least a first alert responsive to receiving the at least the first electrical alert attention signal; and~~
~~a first waterproof receiver housing adapted to carry at least one of the first receiving element, the first receiver and the at least the first alert device.~~

5

141. (New) The underwater alert system according to claim 140, wherein at least one of the first receiver assembly and the second receiver assembly further comprises:

at least a first alert device electrically adapted to generate at least a first alert responsive to receiving the at least one wireless signal.

10

~~142~~. (Currently Amended) The underwater alert system according to claim ~~133~~ 141, wherein the at least the first alert device further comprises:

a visual alert device adapted to generate a visual alert, as the at least the first alert, that ~~the second~~ a diver can see.

15

~~143~~. (Currently Amended) The underwater alert system according to claim ~~134~~ 142, wherein the visual alert device further comprises:

a first light source adapted to generate a visible light signal, as the visual alert.

20

~~144~~. (Currently Amended) The underwater alert system according to claim ~~134~~ 142, wherein the visual alert device further comprises:

a first display adapted to display the first dive computer data, as the visual alert.

25

~~145~~. (Currently Amended) The underwater alert system according to claim ~~133~~ 141, wherein the at least the first alert device further comprises:

an audible alert device adapted to generate an audible alert, as the at least the first alert, that ~~the second~~ a diver can hear.

30

138146. (Currently Amended) The underwater alert system according to claim 137-145, wherein the audible alert device further comprises:

an electro-acoustic transducer adapted to generate an audible acoustic signal, as the audible alert.

139147. (Currently Amended) The underwater alert system according to claim 133-141, wherein the at least the first alert device further comprises:

a tactile alert device adapted to generate a tactile alert, as the at least the first alert, that the second diver can feel.

140148. (Currently Amended) The underwater alert system according to claim 139-147, wherein the tactile alert device further comprises:

a vibrator adapted to generate a vibration signal, as the tactile alert.

141149. (Currently Amended) The underwater alert system according to claim 133-141 further comprising:

a second transmitter assembly, adapted to be carried by the second diver while the second diver is underwater, for transmitting a third wireless signal responsive to receiving second dive computer data related to at least one of the second diver's body, equipment, and environment; and

a third receiver assembly, adapted to be carried by the first diver while the first diver is underwater, for communicating to the first diver third information related to the second dive computer data responsive to receiving the third wireless signal over a third wireless communication link, having a third range, between the second transmitter assembly and the third receiver assembly.

a second transmitter assembly, adapted to be carried by the second diver, including:

a second dive computer adapted to generate second dive computer data responsive to receiving information related to at least one of the second diver's body, equipment, and environment;

a second transmitter electrically coupled to the second dive computer and adapted to generate at least a second electrical transmit signal responsive to receiving the second dive computer data, respectively;

~~_____ a second transmitting element electrically coupled to the second transmitter and adapted to generate at least a second wireless signal responsive to receiving the at least the second electrical transmit signal, respectively; and~~

~~_____ a second waterproof transmitter housing adapted to carry at least one of the second dive computer, the second transmitter, and the second transmitting element; and~~

~~_____ a second receiver assembly, adapted to be carried by the first diver, including:~~

~~_____ a second receiving element adapted to generate at least a second electrical receive signal responsive to receiving the at least the second wireless signal, respectively;~~

~~_____ a second receiver electrically coupled to the second receiving element and adapted to generate at least a second electrical alert attention signal responsive to receiving the at least the second electrical receive signal, respectively;~~

~~_____ at least a second alert device electrically coupled to the second receiver and adapted to generate at least a second alert responsive to receiving the at least the second electrical alert attention signal; and~~

~~_____ a second waterproof receiver housing adapted to carry at least one of the second receiving element, the second receiver and the at least the second alert device.~~

150. (New) The underwater alert system according to claim 149, wherein the second receiver assembly is formed separate from the third receiver assembly to provide two receiver assemblies.

151. (New) The underwater alert system according to claim 149, wherein the second receiver assembly is integrally formed with the third receiver assembly to provide one receiver assembly.

142152. (Currently Amended) The underwater alert system according to claim ~~141~~ 151, wherein the ~~at least the second alert device~~ one receiver assembly further comprises:

a second display adapted to display ~~the second dive computer data~~ at least one of the second information and the third information.

443153. (Currently Amended) The underwater alert system according to claim 442152, wherein ~~at least one of the first display and the second display displays~~ is adapted to display at least one of:

all of each of the ~~first computer data~~ second information and the ~~second computer data~~ third information at the same time;

5 a portion of each of the ~~first computer data~~ second information and the ~~second computer data~~ third information at the same time;

at least a portion of the ~~first computer data~~ second information at a first time and at least a portion of the ~~second computer data~~ third information at a second time, different from the first time.

10 444154. (Currently Amended) The underwater alert system according to claim 441149, ~~wherein~~ at least one of:

~~wherein the first waterproof transmitter housing assembly and the second third waterproof receiver housing assembly~~ are integrally formed together to provide a first transceiver housing assembly adapted to be carried by the first diver, and

15 ~~wherein the second waterproof transmitter assembly housing and the first waterproof receiver assembly housing~~ are integrally formed together to provide a second transceiver assembly housing adapted to be carried by the second diver.

20 445155. (Currently Amended) The underwater alert system according to claim 441154, ~~wherein~~ at least one of:

~~wherein the first transceiver assembly housing~~ is integrally formed with a second mask adapted to be worn by the first diver, and

~~wherein the second transceiver assembly housing~~ is integrally formed with a first mask adapted to be worn by the second diver.

25 446156. (Currently Amended) The underwater alert system according to claim 433140 further comprising at least one of:

a first attachment mechanism adapted to permit the first ~~waterproof receiver assembly housing~~ to be mechanically coupled to a first mask adapted to be worn by the second diver; and

30 a second attachment mechanism adapted to permit the second receiver assembly to be mechanically coupled to a second mask adapted to be worn by the first diver.

447157. (Currently Amended) The underwater alert system according to claim ~~446-156~~, wherein at least one of:

~~wherein~~ the first attachment mechanism further comprises:

5 ~~_____~~ a first bracket adapted to be carried by the first mask and having a first mounting interface adapted to mechanically engage and disengage a first mounting interface on the first ~~waterproof-receiver housing assembly~~ to permit the first ~~waterproof-receiver housing assembly~~ to be attached to and removed from, respectively, the first bracket, and

~~_____~~ the second attachment mechanism further comprises:

10 ~~_____~~ a second bracket adapted to be carried by the second mask and having a first mounting interface adapted to mechanically engage and disengage a first mounting interface on the second receiver assembly to permit the second receiver assembly to be attached to and removed from, respectively, the second bracket.

15 448158. (Currently Amended) The underwater alert system according to claim ~~447-157~~, wherein at least one of:

~~_____~~ wherein the first bracket further comprises:

~~_____~~ a second mounting interface having an adhesive disposed thereon to permit the second mounting interface of the first bracket to be mechanically coupled to the first mask, and

20 ~~_____~~ the second bracket further comprises:

~~_____~~ a second mounting interface having an adhesive disposed thereon to permit the second mounting interface of the second bracket to be mechanically coupled to the second mask.

25 449159. (Currently Amended) The underwater alert system according to claim ~~447-157~~, wherein at least one of:

~~_____~~ wherein the first bracket is integrally formed with the first mask, and

~~_____~~ the second bracket is integrally formed with the second mask.

30

~~450160.~~ (Currently Amended) The underwater alert system according to claim ~~433140~~, wherein at least one of:

_____ the first ~~waterproof~~ receiver assembly housing is integrally formed with the a first mask adapted to be worn by the second diver, and

5 _____ the second receiver assembly is integrally formed with a second mask adapted to be worn by the first diver.

~~451161.~~ (Currently Amended) The underwater alert system according to claim ~~433140~~, wherein at least one of:

10 ~~wherein~~ the first transmitter assembly further comprises:

_____ a first transmitter identity selection device adapted to provide the first transmitter assembly with at least a first transmitter identity, and

~~wherein~~ the first receiver assembly further comprises:

15 _____ a first receiver identity selection device adapted to provide the first receiver assembly with the at least the first transmitter identity to permit the first receiver assembly to communicate with the first transmitter assembly, and

_____ the second receiver assembly further comprises:

20 _____ a second receiver identity selection device adapted to provide the second receiver assembly with the at least the first transmitter identity to permit the second receiver assembly to communicate with the first transmitter assembly.

~~452162.~~ (Currently Amended) The underwater alert system according to claim ~~433140~~, wherein at least one of:

~~wherein~~ the first transmitter assembly further comprises:

25 _____ a first power supply adapted to provide a first supply of electrical power; and

_____ a first power switch adapted to electrically couple the first supply of electrical power to at least one of the first dive computer, the first transmitter and the first transmitting element responsive to the first power switch being actuated the first transmitter assembly; and

~~wherein~~ the first receiver assembly further comprises:

30 _____ a second power supply adapted to provide a second supply of electrical power; and

a second power switch adapted to electrically couple the second supply of electrical power to ~~at least one of the first receiving element, the first receiver and the at least the first alert device responsive to the second power switch being actuated~~ the first receiver assembly, and

the second receiver assembly further comprises:

5 a third power supply adapted to provide a third supply of electrical power; and

a third power switch adapted to electrically couple the third supply of electrical power to the second receiver assembly.

10 ~~+53163.~~ (Currently Amended) The underwater alert system according to claim ~~+52-162~~, wherein at least one of the first power switch, ~~and the second power switch, and the third power switch~~ further comprises:

a water-activated switch adapted to be actuated responsive to the water-activated switch being located underwater.

15 ~~+54164.~~ (Currently Amended) The underwater alert system according to claim ~~+33-140~~, wherein the first transmitter assembly generates the at least ~~a first electrical transmit one~~ wireless signal responsive to receiving the first dive computer data, ~~respectively,~~ having an undesirable, predetermined value.

20 ~~+55165.~~ (Currently Amended) The underwater alert system according to claim ~~+33-140~~, wherein the first transmitter assembly generates the at least ~~a first electrical transmit one~~ wireless signal representing the first dive computer data, ~~respectively,~~ responsive to receiving the first dive computer data, ~~respectively.~~

25 156 to 157 (Cancelled)

~~+58166.~~ (Currently Amended) The underwater alert system according to claim ~~+33-140~~ wherein the first dive computer data further comprises at least one of:

30 dive table time limits, dive time duration, dive depth, air supply level, direction, distance, water temperature, ascent rate, heart rate, and breathing rate.

159167. (Currently Amended) An underwater alert system comprising:

a ~~first~~ at least one transmitter assembly, adapted to be carried by a first diver, including:

a ~~first~~ at least one dive computer adapted to generate first dive computer data responsive to receiving information related to at least one of the first diver's body, equipment, and environment;

5 at least one ~~a first~~ transmitter electrically coupled to the at least one ~~first~~ dive computer and adapted to generate at least a ~~first~~ one electrical transmit signal, representing the first dive computer data, responsive to receiving the first dive computer data, ~~respectively~~;

10 at least one ~~a first~~ transmitting element electrically coupled to the at least one ~~first~~ transmitter and adapted to generate at least a ~~first~~ one wireless signal responsive to receiving the at least ~~the first~~ one electrical transmit signal, ~~respectively~~; and

at least one ~~a first~~ waterproof transmitter housing adapted to carry at least one of the at least one ~~first~~ dive computer, the at least one ~~first~~ transmitter, and the at least one ~~first~~ transmitting element; and

a first receiver assembly, adapted to be carried by a second diver, including:

15 a first receiving element adapted to generate at least a first electrical receive signal responsive to receiving the at least ~~the first~~ one wireless signal over a first wireless communication link, having a first range, between the at least one transmitter assembly and the first receiver assembly, respectively;

20 a first receiver electrically coupled to the first receiving element and adapted to generate at least a first electrical alert attention signal responsive to receiving the at least the first electrical receive signal, ~~respectively~~;

at least a first alert device electrically coupled to the first receiver and adapted to generate at least a first alert responsive to receiving the at least the first electrical alert attention signal, wherein the at least the first alert device further comprises:

25 _____ a first visual alert device adapted to generate a first visual alert, as the at least the first alert, that the second diver can see, wherein the first visual alert device further comprises:

_____ a first display adapted to display the first dive computer data, as the visual alert; and

30 a first waterproof receiver housing adapted to carry at least one of the first receiving element, the first receiver, and the at least the first alert device;

~~wherein the first transmitter and the first receiver communicate over a first wireless communication link having a first range between the first diver and the second diver; and~~

a second receiver assembly, adapted to be carried by the first diver, including:

a second receiving element adapted to generate at least a second electrical receive signal responsive to receiving the at least one wireless signal over a second wireless communication link, having a second range, between the at least one transmitter assembly and the second receiver assembly;

a second receiver electrically coupled to the second receiving element and adapted to generate at least a second electrical alert attention signal responsive to receiving the at least the second electrical receive signal;

at least a second alert device electrically coupled to the second receiver and adapted to generate at least a second alert responsive to receiving the at least the second electrical alert attention signal, wherein the at least the second alert device further comprises:

a second visual alert device adapted to generate a second visual alert, as the at least the second alert, that the first diver can see, wherein the second visual alert device further comprises:

a second display adapted to display the dive computer data, as the second visual alert; and

a second waterproof receiver housing adapted to carry at least one of the second receiving element, the second receiver, and the at least the second alert device.

~~160168: (Currently Amended) The underwater alert system according to claim 159-167 further comprising:~~

a second transmitter assembly, adapted to be carried by the second diver, including:

a second dive computer adapted to generate second dive computer data responsive to receiving information related to at least one of the second diver's body, equipment, and environment;

a second transmitter electrically coupled to the second dive computer and adapted to generate at least a second electrical transmit signal responsive to receiving the second dive computer data, respectively;

a second transmitting element electrically coupled to the second transmitter and adapted to generate at least a second wireless signal responsive to receiving the at least the second electrical transmit signal, ~~respectively~~; and

5 a second waterproof transmitter housing adapted to carry at least one of the second dive computer, the second transmitter, and the second transmitting element; and

a ~~second-third~~ receiver assembly, adapted to be carried by the first diver, and adapted to be integrally formed with the second receiver assembly to provide a single receiver assembly or separately formed the second receiver assembly to provide two receiver assemblies, including:

10 a ~~third second~~-receiving element adapted to generate at least a ~~third second~~-electrical receive signal responsive to receiving the at least the second wireless signal, ~~respectively~~;

a ~~third second~~-receiver electrically coupled to the ~~third second~~-receiving element and adapted to generate at least a ~~third second~~-electrical alert attention signal responsive to receiving the at least the ~~third second~~-electrical receive signal, ~~respectively~~;

15 at least a ~~third second~~-alert device electrically coupled to the ~~third second~~-receiver and adapted to generate at least a ~~third second~~-alert responsive to receiving the at least the ~~third second~~-electrical alert attention signal, wherein the at least the ~~third second~~-alert device further comprises:

a second display adapted to display the second dive computer data; and

a ~~third second~~-waterproof receiver housing adapted to carry at least one of the ~~third second~~-receiving element, the ~~third second~~-receiver, and the at least the ~~third second~~-alert device.

20 ~~16+169.~~ (Currently Amended) The underwater alert system according to claim ~~160-168~~ wherein at least one of the first display and the second display displays at least one of:

all of each of the first ~~dive~~ computer data and the second computer data at the same time;

25 a portion of each of the first ~~dive~~ computer data and the second ~~dive~~ computer data at the same time;

at least a portion of the first ~~dive~~ computer data at a first time and at least a portion of the second ~~dive~~ computer data at a second time, different from the first time.

30

~~162~~170. (Currently Amended) The underwater alert system according to claim ~~160~~168:

wherein the first waterproof transmitter housing and the second waterproof receiver housing are integrally formed together to provide a first transceiver housing adapted to be carried by the first diver, and

5 wherein the second waterproof transmitter housing and the first waterproof receiver housing are integrally formed together to provide a second transceiver housing adapted to be carried by the second diver.

~~163~~171. (Currently Amended) The underwater alert system according to claim ~~159~~167:

10 wherein the at least one ~~first~~-transmitter assembly further comprises a ~~first~~-transmitter identity selection device adapted to provide the ~~first~~-at least one transmitter assembly with at least a ~~first~~-transmitter identity, and

wherein the first receiver assembly further comprises a ~~first~~-receiver identity selection device adapted to provide the first receiver assembly with the at least the ~~first~~-transmitter identity to permit
15 the first receiver assembly to communicate with the ~~first~~-at least one transmitter assembly.

164. (Cancelled)

~~165~~172. (Currently Amended) The underwater alert system according to claim ~~159~~167, wherein
20 the first dive computer data further comprises at least one of:

dive table time limits, dive time duration, dive depth, air supply level, direction, distance, water temperature, ascent rate, heart rate, and breathing rate.

466173. (Currently Amended) An underwater alert system comprising:

_____ at least a first transmitter assembly, adapted to be carried by a first diver while the first diver is underwater, for transmitting at least one wireless signal responsive to receiving first dive computer data, related to at least one of the first diver's body, equipment, and environment, having a predetermined value; and

_____ a first receiver assembly, adapted to be carried by a second diver while the second diver is underwater, for communicating to the second diver first information related to the first dive computer data responsive to receiving the at least one wireless signal over a first wireless communication link, having a first range, between the at least one transmitter assembly and the first receiver assembly.

_____ a first transmitter assembly, adapted to be carried by a first diver, including:

_____ a first dive computer adapted to generate first dive computer data responsive to receiving information related to at least one of the first diver's body, equipment, and environment;

_____ a first transmitter electrically coupled to the first dive computer and adapted to generate at least a first predetermined electrical transmit signal responsive to receiving the first dive computer data, respectively, having an undesirable, predetermined value;

_____ a first transmitting element electrically coupled to the first transmitter and adapted to generate at least a first predetermined wireless signal responsive to receiving the at least the first predetermined electrical transmit signal, respectively; and

_____ a first waterproof transmitter housing adapted to carry at least one of the first dive computer, the first transmitter and the first transmitting element; and

_____ a first receiver assembly, adapted to be carried by a second diver, including:

_____ a first receiving element adapted to generate at least a first electrical receive signal responsive to receiving the at least the first predetermined wireless signal, respectively;

_____ a first receiver electrically coupled to the first receiving element and adapted to generate at least a first predetermined electrical alert attention signal responsive to receiving the at least the first predetermined electrical receive signal, respectively;

_____ at least a first alert device electrically coupled to the first receiver and adapted to generate at least a first predetermined alert responsive to receiving the at least the first predetermined electrical alert attention signal; and

~~_____ a first waterproof receiver housing adapted to carry at least one of the first receiving element, the first receiver and the at least the first alert device,~~
~~_____ wherein the first transmitter and the first receiver communicate over a first wireless communication link having a first range between the first diver and the second diver.~~

5

174. (New) The underwater alert system according to claim 173 further comprising:

a second receiver assembly, adapted to be carried by the first diver while the first diver is underwater, for communicating to the first diver second information related to the first dive computer data responsive to receiving the at least one wireless signal over a second wireless communication link, having a second range, between the at least one transmitter assembly and the second receiver assembly.

10

175. (New) The underwater alert system according to claim 173, wherein the at least one wireless signal is predetermined.

15

176. (New) The underwater alert system according to claim 173, wherein the at least one wireless signal represents the first dive computer data.

177. (New) The underwater alert system according to claim 173, wherein the first receiver assembly further comprises:

20

at least a first alert device electrically adapted to generate at least a first alert responsive to receiving the at least one wireless signal.

178. (New) The underwater alert system according to claim 177, wherein the first alert is predetermined.

25

~~167~~179. (Currently Amended) The underwater alert system according to claim ~~166~~177, wherein the at least the first alert device further comprises:

a visual alert device adapted to generate a ~~predetermined~~ visual alert, as the at least the first ~~predetermined~~ alert, that the second diver can see.

30

468180. (Currently Amended) The underwater alert system according to claim ~~467-179~~, wherein the visual alert device further comprises:

a first light source adapted to generate a ~~predetermined~~-visible light signal, as the ~~predetermined~~-visual alert.

469181. (Currently Amended) The underwater alert system according to claim ~~466-177~~, wherein the at least the first alert device further comprises:

an audible alert device adapted to generate a ~~predetermined~~-audible alert, as the at least the first ~~predetermined~~-alert; that the second diver can hear.

470182. (Currently Amended) The underwater alert system according to claim ~~469-181~~, wherein the audible alert device further comprises:

an electro-acoustic transducer adapted to generate a ~~predetermined~~-audible acoustic signal, as the ~~predetermined~~-audible alert.

471183. (Currently Amended) The underwater alert system according to claim ~~466-177~~, wherein the at least the first alert device further comprises:

a tactile alert device adapted to generate a ~~predetermined~~-tactile alert, as the at least the first ~~predetermined~~-alert, that the second diver can feel.

472184. (Currently Amended) The underwater alert system according to claim ~~471-183~~, wherein the tactile alert device further comprises:

a vibrator adapted to generate a ~~predetermined~~-vibration signal, as the ~~predetermined~~-tactile alert.

473185. (Currently Amended) The underwater alert system according to claim ~~466-173~~ further comprising:

a second transmitter assembly, adapted to be carried by the second diver while the second diver is underwater, for transmitting a third wireless signal responsive to receiving second dive computer data, related to at least one of the second diver's body, equipment, and environment, having a predetermined value; and

a third receiver assembly, adapted to be carried by the first diver while the first diver is underwater, for communicating to the first diver third information related to the second dive computer data responsive to receiving the third wireless signal over a third wireless communication link, having a third range, between the second transmitter assembly and the third receiver assembly.

5 ~~a second transmitter assembly, adapted to be carried by the second diver, including:~~

~~— a second dive computer adapted to generate second dive computer data responsive to receiving information related to at least one of the second diver's body, equipment, and environment;~~

10 ~~— a second transmitter electrically coupled to the second dive computer and adapted to generate at least a second predetermined electrical transmit signal responsive to receiving the second dive computer data, respectively;~~

~~— a second transmitting element electrically coupled to the second transmitter and adapted to generate at least a second predetermined wireless signal responsive to receiving the at least the second predetermined electrical transmit signal, respectively; and~~

15 ~~— a second waterproof transmitter housing adapted to carry at least one of the second dive computer, the second transmitter, and the second transmitting element; and~~

~~— a second receiver assembly, adapted to be carried by the first diver, including:~~

~~— a second receiving element adapted to generate at least a second electrical receive signal responsive to receiving the at least the second predetermined wireless signal, respectively;~~

20 ~~— a second receiver electrically coupled to the second receiving element and adapted to generate at least a second predetermined electrical alert attention signal responsive to receiving the at least the second predetermined electrical receive signal, respectively;~~

~~— at least a second alert device electrically coupled to the second receiver and adapted to generate at least a second predetermined alert responsive to receiving the at least the second predetermined electrical alert attention signal; and~~

25 ~~— a second waterproof receiver housing adapted to carry at least one of the second receiving element, the second receiver and the at least the second alert device.~~

30

474186. (Currently Amended) The underwater alert system according to claim 473185;

wherein the first ~~waterproof-transmitter housing-assembly~~ and the second ~~waterproof receiver assembly housing~~ are integrally formed together to provide a first transceiver assembly ~~housing~~ adapted to be carried by the first diver, and

5 wherein the second ~~waterproof-transmitter assembly housing~~ and the first ~~waterproof receiver assembly housing~~ are integrally formed together to provide a second transceiver assembly ~~housing~~ adapted to be carried by the second diver.

475187. (Currently Amended) The underwater alert system according to claim 474186;

10 wherein the first transceiver assembly housing is integrally formed with a second mask adapted to be worn by the first diver, and

wherein the second transceiver assembly housing is integrally formed with a first mask adapted to be worn by the second diver.

15 476188. (Currently Amended) The underwater alert system according to claim 466173;

wherein the first transmitter assembly further comprises a first transmitter identity selection device adapted to provide the first transmitter assembly with at least a first transmitter identity, and

20 wherein the first receiver assembly further comprises a first receiver identity selection device adapted to provide the first receiver with the at least the first transmitter identity to permit the first receiver assembly to communicate with the first transmitter assembly.

177. (Cancelled)

478189. (Currently Amended) The underwater alert system according to claim 466173, wherein

25 the first dive computer data further comprises at least one of:

dive table time limits, dive time duration, dive depth, air supply level, direction, distance, water temperature, ascent rate, heart rate, and breathing rate.

190. (New) The underwater alert system according to claim 173,
wherein the at least the first transmitter assembly further comprises:

5 a first dive computer adapted to generate the first dive computer data responsive to receiving information related to at least one of the first diver's body, equipment, and environment;

a first transmitter electrically coupled to the first dive computer and adapted to generate at least one electrical transmit signal responsive to receiving the first dive computer data, respectively, having the predetermined value;

10 a first transmitting element electrically coupled to the first transmitter and adapted to generate the at least one wireless signal responsive to receiving the at least one electrical transmit signal, respectively; and

a first waterproof transmitter housing adapted to carry at least one of the first dive computer, the first transmitter, and the first transmitting element; and

a first receiver assembly, adapted to be carried by a second diver, including:

15 a first receiving element adapted to generate at least one electrical receive signal responsive to receiving the at least one wireless signal, respectively;

a first receiver electrically coupled to the first receiving element and adapted to generate at least one electrical alert attention signal responsive to receiving the at least one electrical receive signal, respectively;

20 at least a first alert device electrically coupled to the first receiver and adapted to generate at least one alert responsive to receiving the at least one electrical alert attention signal; and

a first waterproof receiver housing adapted to carry at least one of the first receiving element, the first receiver, and the at least the first alert device.

479191. (Currently Amended) ~~In an~~An underwater alert system comprising:

at least a one transmitter assembly, adapted to be carried by a first diver while the first diver is underwater, for transmitting at least one wireless signal responsive to receiving first dive computer data related to at least one of the first diver's body, equipment, and environment;

5 wherein the at least a one transmitter assembly is adapted to transmit the at least one wireless signal to a first receiver assembly, adapted to be carried by a second diver while the second diver is underwater, for communicating to the second diver first information related to the first dive computer data responsive to receiving the at least one wireless signal over a first wireless communication link, having a first range, between the at least one transmitter assembly and the first receiver assembly; and

10 wherein the at least a one transmitter assembly is adapted to transmit the at least one wireless signal to a second receiver assembly, adapted to be carried by the first diver while the first diver is underwater, for communicating to the first diver second information related to the first dive computer data responsive to receiving the at least one wireless signal over a second wireless communication link, having a second range, between the at least one transmitter assembly and the
15 second receiver assembly.

~~including a first transmitter assembly adapted to be carried by a first diver and a first receiver assembly adapted to be carried by a second diver, the first transmitter assembly comprising:~~

20 ~~—— a first dive computer adapted to generate first dive computer data responsive to receiving information related to at least one of the first diver's body, equipment, and environment;~~

~~—— a first transmitter electrically coupled to the first dive computer and adapted to generate at least a first electrical transmit signal responsive to receiving the first dive computer data, respectively;~~

25 ~~—— a first transmitting element electrically coupled to the first transmitter and adapted to generate at least a first wireless signal responsive to receiving the at least the first electrical transmit signal, respectively; and~~

~~—— a first waterproof transmitter housing adapted to carry at least one of the first dive computer, the first transmitter and the first transmitting element,~~

30 ~~—— wherein the first receiver assembly includes:~~

~~_____ a first receiving element adapted to generate at least a first electrical receive signal responsive to receiving the at least the first wireless signal, respectively;~~

~~_____ a first receiver electrically coupled to the first receiving element and adapted to generate at least a first electrical alert attention signal responsive to receiving the at least the first electrical receive signal, respectively;~~

~~_____ at least a first alert device electrically coupled to the first receiver and adapted to generate at least a first alert responsive to receiving the at least the first electrical alert attention signal; and~~

~~_____ a first waterproof receiver housing adapted to carry at least one of the first receiving element, the first receiver, and the at least the first alert device.~~

180192. (Currently Amended) ~~In an~~ An underwater alert system including at least one transmitter assembly, adapted to be carried by a first diver while the first diver is underwater, for transmitting at least one wireless signal responsive to receiving first dive computer data related to at least one of the first diver's body, equipment, and environment, the underwater alert system comprising:

5 a first receiver assembly, adapted to be carried by a second diver while the second diver is underwater, for communicating to the second diver first information related to the first dive computer data responsive to receiving at least one wireless signal over a first wireless communication link, having a first range, between the at least one transmitter assembly and the first receiver assembly; and

10 a second receiver assembly, adapted to be carried by the first diver while the first diver is underwater, for communicating to the first diver second information related to the first dive computer data responsive to receiving the at least one wireless signal over a second wireless communication link, having a second range, between the at least one transmitter assembly and the second receiver assembly.

15 ~~including a first transmitter assembly adapted to be carried by a first diver and a first receiver assembly adapted to be carried by a second diver, the first receiver assembly comprising:~~

~~—— a first receiving element adapted to generate at least a first electrical receive signal responsive to receiving at least a first wireless signal, respectively, representing information related to at least one of the first diver's body, equipment, and environment, generated by the transmitter assembly;~~

20 ~~—— a first receiver electrically coupled to the first receiving element and adapted to generate at least a first electrical alert attention signal responsive to receiving the at least the first electrical receive signal, respectively;~~

~~—— at least a first alert device electrically coupled to the first receiver and adapted to generate at least a first alert responsive to receiving the at least the first electrical alert attention signal; and~~

25 ~~—— a first waterproof receiver housing adapted to carry at least one of the first receiving element, the first receiver and the at least the first alert device.~~

~~181~~193. (Currently Amended) An underwater alert system comprising:

at least one means for transmitting, adapted to be carried by a first diver while the first diver is underwater, at least one wireless signal responsive to receiving first dive computer data related to at least one of the first diver's body, equipment, and environment;

5 first means for receiving, adapted to be carried by a second diver while the second diver is underwater, the at least one wireless signal over a first wireless communication link, having a first range, between the at least one means for transmitting and the first means for receiving to communicate to the second diver first information related to the first dive computer data; and

second means for receiving, adapted to be carried by the first diver while the first diver is
10 underwater, the at least one wireless signal over a second wireless communication link, having a second range, between the at least one means for transmitting and the second means for receiving to communicate to the first diver second information related to the first dive computer data.

~~means for providing a first transmitter assembly, adapted to be carried by a first diver, including:~~

15 ~~means for generating first dive computer data responsive to receiving information related to at least one of the first diver's body, equipment, and environment;~~

~~means for generating at least a first electrical transmit signal responsive to receiving the first dive computer data, respectively;~~

~~means for generating at least a first wireless signal responsive to receiving the at least the~~
20 ~~first electrical transmit signal, respectively; and~~

~~means for carrying at least one of the first dive computer, the first transmitter and the first transmitting element; and~~

~~means for providing a first receiver assembly, adapted to be carried by a second diver, including:~~

25 ~~means for generating at least a first electrical receive signal responsive to receiving the at least the first wireless signal, respectively;~~

~~means for generating at least a first electrical alert attention signal responsive to receiving the at least the first electrical receive signal, respectively;~~

~~means for generating at least a first alert responsive to receiving the at least the first~~
30 ~~electrical alert attention signal; and~~

~~means for carrying at least one of the first receiving element, the first receiver and the at least the first alert device.~~

194. (New) The underwater alert system according to any one of claims 140 to 193, wherein the first range is substantially longer than the second range.

195. (New) The underwater alert system according to any one of claims 140 to 193, wherein the first range is substantially the same as the second range.

196. (New) The underwater alert system according to any one of claims 140 to 193, wherein the at least one wireless signal further comprises:

a first wireless signal adapted to be transmitted over the first wireless communication link;

and

a second wireless signal, substantially the same as the first wireless signal, adapted to be transmitted over the second wireless communication link.

197. (New) The underwater alert system according to any one of claims 140 to 193, wherein the at least one wireless signal further comprises:

a first wireless signal adapted to be transmitted over the first wireless communication link;

and

a second wireless signal, substantially the different from the first wireless signal, adapted to be transmitted over the second wireless communication link.

198. (New) The underwater alert system according to any one of claims 140 to 192, wherein the at least one transmitter assembly further comprises:

a first transmitter assembly for transmitting a first wireless signal representing the at least one wireless signal, and

a second transmitter assembly for transmitting a second wireless signal representing the at least one wireless signal.

199. (New) An underwater alert system according to any one of claims 140 to 192,

wherein the at least one transmitter assembly further comprises:

at least one dive computer adapted to generate the first dive computer data responsive to receiving information related to at least one of the diver's body, equipment, and environment;

5 at least one transmitter electrically coupled to the at least one dive computer and adapted to generate at least one electrical transmit signal responsive to receiving the first dive computer data;

10 at least one transmitting element electrically coupled to the at least one transmitter and adapted to generate the at least one wireless signal responsive to receiving the at least one electrical transmit signal; and

at least one waterproof transmitter housing adapted to carry at least one of the at least one dive computer, the at least one transmitter, and the at least one transmitting element,

wherein the first receiver assembly further comprises:

15 a first receiving element adapted to generate at least a first electrical receive signal responsive to receiving the at least one wireless signal;

a first receiver electrically coupled to the first receiving element and adapted to generate at least a first electrical alert attention signal responsive to receiving the at least the first electrical receive signal;

20 a first alert device electrically coupled to the first receiver and adapted to generate at least a first alert responsive to receiving the at least the first electrical alert attention signal; and

a first waterproof receiver housing adapted to carry at least one of the first receiving element, the first receiver, and the first alert device, and

wherein the second receiver assembly further comprises:

25 a second receiving element adapted to generate at least a second electrical receive signal responsive to receiving the at least one wireless signal;

a second receiver electrically coupled to the second receiving element and adapted to generate at least a second electrical alert attention signal responsive to receiving the at least the second electrical receive signal,

30 a second alert device electrically coupled to the second receiver and adapted to generate at least a second alert responsive to receiving the at least the second electrical alert attention signal; and

Amendment

SN: 09/862,914; Docket Number: DJM-0001; Magine, et al.

a second waterproof receiver housing adapted to carry at least one of the second receiving element, the second receiver, and the second alert device.

~~182200.~~ (Currently Amended) An underwater alert system comprising:

a transmitter assembly, adapted to be carried by a first diver while the first diver is underwater, for transmitting a wireless signal responsive to receiving dive computer data related to at least one of the first diver's body, equipment, and environment; and

5 a receiver assembly, adapted to be carried by a mask worn by a second diver while the second diver is underwater, for communicating to the second diver information related to the dive computer data responsive to receiving the wireless signal.

~~a first transmitter assembly, adapted to be carried by a first person while the first person is underwater, for transmitting a wireless signal responsive to receiving data related to at least one of~~
10 ~~the first person's body, equipment, and environment; and~~

~~— a first receiver assembly, adapted to be carried by a second person while the second person is underwater, for communicating to the second person information related to the data responsive to receiving the wireless signal.~~

15 201. (New) The underwater alert system according to claim 200 further comprising:

an attachment mechanism adapted to permit the receiver assembly to be mechanically coupled to the mask.

20 202. (New) The underwater alert system according to claim 201, wherein the attachment mechanism further comprises:

a bracket adapted to be carried by the mask and having a first mounting interface adapted to mechanically engage and disengage a first mounting interface on the receiver assembly to permit the receiver assembly to be attached to and removed from, respectively, the bracket.

25 203. (New) The underwater alert system according to claim 202, wherein the bracket further comprises:

a second mounting interface having an adhesive disposed thereon to permit the second mounting interface of the bracket to be mechanically coupled to the mask.

30 204. (New) The underwater alert system according to claim 202, wherein the bracket is integrally formed with the mask.

Amendment

SN: 09/862,914; Docket Number: DJM-0001; Magine, et al.

205. (New) The underwater alert system according to claim 200, wherein the receiver assembly is integrally formed with the mask.

206. (New) An underwater alert system comprising:

a transmitter assembly, adapted to be carried by a first diver while the first diver is underwater, for transmitting a wireless signal responsive to receiving dive computer data related to at least one of the first diver's body, equipment, and environment; and

5 a receiver assembly, adapted to be carried by a second diver while the second diver is underwater, for communicating to the second diver information related to the dive computer data responsive to receiving the wireless signal, wherein the receiver assembly includes:

a tactile alert device adapted to generate a tactile alert, representing the information, which the second diver can feel.

10 207. (New) The underwater alert system according to claim 206, wherein the tactile alert device further comprises:

a vibrator adapted to generate a vibration signal representing the tactile alert.

15 208. (New) An underwater alert system according to claim 206,

wherein the transmitter assembly further comprises:

a dive computer adapted to generate the dive computer data responsive to receiving information related to at least one of the first diver's body, equipment, and environment;

20 a transmitter electrically coupled to the first dive computer and adapted to generate an electrical transmit signal responsive to receiving the dive computer data;

a transmitting element electrically coupled to the first transmitter and adapted to generate the wireless signal responsive to receiving the electrical transmit signal; and

a waterproof transmitter housing adapted to carry at least one of the dive computer, the transmitter, and the transmitting element; and

25 wherein the receiver assembly further comprises:

a receiving element adapted to generate an electrical receive signal responsive to receiving the wireless signal;

a receiver electrically coupled to the receiving element and adapted to generate an electrical alert attention signal responsive to receiving the electrical receive signal; and

30 a waterproof receiver housing adapted to carry at least one of the receiving element, the receiver, and the tactile alert device.

209. (New) An underwater alert system comprising:

a first transmitter assembly, adapted to be carried by a first diver while the first diver is underwater, for transmitting a first wireless signal responsive to receiving first dive computer data related to at least one of the first diver's body, equipment, and environment;

5 a first receiver assembly, adapted to be carried by a second diver while the second diver is underwater, for communicating to the second diver first information related to the first dive computer data responsive to receiving the first wireless signal;

a second transmitter assembly, adapted to be carried by the second diver while the second diver is underwater, for transmitting a second wireless signal responsive to receiving second dive computer data related to at least one of the second diver's body, equipment, and environment; and

10 a second receiver assembly, adapted to be carried by the first diver while the first diver is underwater, for communicating to the first diver second information related to the second dive computer data responsive to receiving the second wireless signal.

15 210. (New) The underwater alert system according to claim 209, wherein at least one of:

the first transmitter assembly and the second receiver assembly are integrally formed together to provide a first transceiver assembly adapted to be carried by the first diver, and

the second transmitter assembly and the first receiver assembly are integrally formed together to provide a second transceiver assembly adapted to be carried by the second diver.

20

211. (New) The underwater alert system according to claim 210, wherein at least one of:

the first transceiver assembly is integrally formed with a second mask adapted to be worn by the first diver, and

the second transceiver assembly is integrally formed with a first mask adapted to be worn by

25 the second diver.

212. (New) The underwater alert system according to claim 209 further comprising at least one of:

a first attachment mechanism adapted to permit the first receiver assembly to be mechanically coupled to a first mask adapted to be worn by the second diver; and

30 a second attachment mechanism adapted to permit the second receiver assembly to be mechanically coupled to a second mask adapted to be worn by the first diver.

213. (New) The underwater alert system according to claim 212, wherein at least one of:
the first attachment mechanism is integrally formed with the first mask, and
the second attachment mechanism is integrally formed with the second mask.

5

214. (New) The underwater alert system according to claim 209, wherein at least one of:
the first receiver assembly is integrally formed with a first mask adapted to be worn by the
second diver, and

the second receiver assembly is integrally formed with a second mask adapted to be worn by

10 the first diver.

215. (New) An underwater alert system comprising:

a transmitter assembly, adapted to be carried by a first diver while the first diver is underwater, for transmitting a wireless signal responsive to receiving dive computer data related to at least one of the first diver's body, equipment, and environment, wherein the transmitter assembly

5 further comprises:

a transmitter power supply adapted to provide electrical power for electrical elements of the transmitter assembly; and

a transmitter power switch adapted to electrically couple the transmitter power supply to electrical elements of the transmitter assembly responsive to the transmitter power switch being
10 actuated; and

a receiver assembly, adapted to be carried by a second diver while the second diver is underwater, for communicating to the second diver information related to the dive computer data responsive to receiving the wireless signal, wherein the receiver assembly further comprises:

a receiver power supply adapted to provide electrical power for electrical elements of
15 the receiver assembly; and

a receiver power switch adapted to electrically couple the receiver power supply to at least one of the electrical elements of the receiver assembly responsive to the receiver power switch being actuated,

wherein at least one of the transmitter power switch and the receiver power switch further
20 comprises:

a water-activated switch adapted to be actuated responsive to the water-activated switch being located underwater.

216. (New) An underwater alert system comprising:

a transmitter assembly, adapted to be carried by a first diver while the first diver is underwater, for transmitting a wireless signal responsive to receiving dive computer data related to at least one of the first diver's body, equipment, and environment, wherein the transmitter assembly further comprises:

a first identity selection device, including a first plurality of discrete hardware elements adapted to control software stored in memory in the transmitter assembly, adapted to program the transmitter assembly with at least one electronic identity responsive to predetermined selections of the first plurality of discrete hardware elements; and

a receiver assembly, adapted to be carried by one of the first diver and a second diver while one of the first diver and the second diver, respectively, is underwater, for communicating to one of the first diver and the second diver, respectively, information related to the dive computer data responsive to receiving the wireless signal, wherein the receiver assembly further comprises:

a second identity selection device, including a second plurality of discrete hardware receiver elements adapted to control software stored in memory in the receiver assembly, adapted to program the receiver assembly with the at least one electronic identity, responsive to predetermined selections of the second plurality of discrete hardware elements, to permit the receiver assembly to communicate with the transmitter assembly.

217. (New) The underwater alert system according to claim 216, wherein the at least one electronic identity further comprises at least one of:

a frequency channel, an address, and a code.

218. (New) The underwater alert system according to claim 206, wherein at least one of the first plurality of discrete hardware elements and the second plurality of discrete hardware elements further comprises:

three discrete hardware elements.

219. (New) An underwater alert system comprising:

a transmitter assembly, adapted to be carried by a diver while the diver is underwater, further comprising:

a first dive computer adapted to generate first dive computer data responsive to receiving first information related to at least one of the diver's body, equipment, and environment;

a transmitter electrically coupled to the first dive computer and adapted to generate at least one electrical transmit signal responsive to receiving the first dive computer data;

a transmitting element electrically coupled to the transmitter and adapted to generate at least one wireless signal responsive to receiving the at least one electrical transmit signal; and

a waterproof transmitter housing adapted to carry at least one of the first dive computer, the transmitter, and the transmitting element; and

a receiver assembly, adapted to be carried by the diver while the diver is underwater, further comprising:

a second dive computer adapted to generate second dive computer data responsive to receiving second information related to at least one of the diver's body, equipment, and environment;

a receiving element adapted to generate at least one electrical receive signal responsive to receiving the at least one wireless signal over a first wireless communication link having a first range, between the transmitter assembly and the receiver assembly;

a receiver electrically coupled to the receiving element and adapted to generate at least one electrical alert attention signal responsive to receiving the at least one electrical receive signal;

a display device electrically coupled to the second dive computer and the receiver and adapted to display at least one of the first dive computer data and the second dive computer data responsive to receiving the at least one electrical alert attention signal and the second dive computer data, respectively; and

a waterproof receiver housing adapted to carry at least one of the second dive computer, the receiving element, the receiver, and the display device.

220. (New) An underwater alert system according to claim 219,

wherein the display device displays the first dive computer data responsive to receiving the at least the first electrical alert attention signal when the receiver assembly is in the first range of the transmitter assembly, which permits the receiver assembly to receive the at least one wireless signal, representing the first dive computer data, and

wherein the display device displays the second dive computer data responsive to receiving the second dive computer data when the receiver assembly is out of the first range of the transmitter assembly, which prevents the receiver assembly from receiving the at least one wireless signal, representing the first dive computer data.

221. (New) An underwater alert system according to claim 220,

wherein the transmitter assembly is carried on an air supply tank carried by the diver, and wherein the receiver assembly is carried by the diver's body or equipment worn by the diver.

222. (New) The underwater alert system according to claim 221 further comprising:

an attachment mechanism, adapted to mechanically couple the receiver assembly to the diver's body or equipment worn by the diver, further comprising at least one of:

a wristband, a strap, a cord, a band, a belt, a clip, and a clamp.

223. (New) The underwater alert system according to claim 222, wherein the receiver assembly is carried by the diver's wrist using the wristband.

224. (New) The underwater alert system according to claim 219, wherein at least one of the first dive computer data and the second dive computer data further comprises at least one of:

dive table time limits, dive time duration, dive depth, air supply level, direction, distance, water temperature, ascent rate, heart rate, and breathing rate.

225. (New) An underwater alert system comprising:

a receiver assembly, adapted to be carried by a first diver while the first diver is underwater, further comprising:

a second dive computer adapted to generate second dive computer data responsive to receiving second information related to at least one of the first diver's body, equipment, and environment;

a receiving element adapted to generate at least one electrical receive signal responsive to receiving from a transmitter assembly at least one wireless signal, representing first dive computer data;

a receiver electrically coupled to the receiving element and adapted to generate at least one electrical alert attention signal responsive to receiving the at least one electrical receive signal;

a display device electrically coupled to the second dive computer and the receiver and adapted to display at least one of first dive computer data and the second dive computer data responsive to receiving the at least one electrical alert attention signal and the second dive computer data, respectively; and

a waterproof receiver housing adapted to carry at least one of the second dive computer, the receiving element, the receiver, and the display device.

226. (New) An underwater alert system according to claim 225,

wherein the transmitter assembly is carried by the first diver, and

wherein the transmitter assembly transmits the at least one wireless signal, representing first dive computer data related to at least one of the first diver's body, equipment, and environment, to the receiver assembly over a first wireless communication link, having a first range, between the transmitter assembly and the receiver assembly.

227. (New) An underwater alert system according to claim 225,
wherein the transmitter assembly is carried by a second diver, and
wherein the transmitter assembly transmits the at least one wireless signal, representing first
dive computer data related to at least one of the second diver's body, equipment, and environment,
5 to the receiver assembly over a second wireless communication link, having a second range,
between the transmitter assembly and the receiver assembly.

228. (New) An underwater alert system according to claim 225,
wherein the display device displays the first dive computer data responsive to receiving the at
10 least the first electrical alert attention signal when the receiver assembly is in range of the transmitter
assembly, which permits the receiver assembly to receive the at least one wireless signal,
representing the first dive computer data, and

wherein the display device displays the second dive computer data responsive to receiving
the second dive computer data when the receiver assembly is out of range of the transmitter
15 assembly, which prevents the receiver assembly from receiving the at least one wireless signal,
representing the first dive computer data.

229. (New) An underwater alert system according to claim 225,
wherein the transmitter assembly is carried on an air supply tank carried a diver, and
20 wherein the receiver assembly is carried by the diver's body or equipment worn by the first
diver.

230. (New) The underwater alert system according to claim 221 further comprising:
an attachment mechanism, adapted to mechanically couple the receiver assembly to the first
25 diver's body or equipment worn by the first diver, further comprising at least one of:
a wristband, a strap, a cord, a band, a belt, a clip, and a clamp.